

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____
T. Salt _____
B. Salt _____
T. Yates 215 _____
T. 7 Rivers _____
T. Queen 935 _____
T. Grayburg _____
T. San Andres 1695 _____
T. Glorieta 3065 _____
T. Paddock _____
T. Blinebry _____
T. Tubb 4550 _____
T. Drinkard _____
T. Abo 5202 _____
T. Wolfcamp 6418 _____
T. Penn _____
T. Cisco (Bough C) 7668 _____

T. Canyon	
T. Strawn	8898
T. Atoka	9278
T. Miss	9890
T. Devonian	
T. Silurian	
T. Montoya	
T. Simpson	
T. McKee	
T. Ellenburger	
T. Gr. Wash	
T. Delaware Sand	
T. Bone Springs	
T.	
T.	
T.	
T.	

Northwestern New Mexico

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____
T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn "A" _____

T. Penn. "B"
T. Penn. "C"
T. Penn. "D"
T. Leadville
T. Madison
T. Elbert
T. McCracken
T. Ignacio Otzte
T. Granite
T.
T.
T.
T.
T.
T.
T.
T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....

No. 3, from.....to.....

No. 2, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2. from.....to.....feet.....

No. 3. from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology
0	740	740	Anhydrite & Dolomite
740	1440	700	Anhydrite, Dolomite, SS, Shale
1440	1850	410	Dolomite
1850	1960	110	No Sample
1960	4540	2580	Dolomite
4540	6580	2040	Dolomite, Sml amnt LS, SS & Shale
6580	9600	3020	LS w/sml amnt shale, chert, Dolo.
9600	9680	80	SS w/ sml amnt LS
9680	9917	237	LS, Shale, SS

From	To	Thickness In Feet	Lithology