

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. ☒ 30-015-30909

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Patterson EL

8. Well No.
3

9. Pool name or Wildcat
Eagle Creek Atoka Morrow East

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3407' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter P : 990 Feet From The South Line and 990 Feet From The East Line

Section 31 Township 17S Range 26E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3407' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Al Springer, Drilling Engineer for Yates Petroleum Corporation received verbal permission from Tim Gum w/OCD-Artesia to change the intermediate string of casing to 9-5/8" 36# from 8-5/8" 24# casing. The 9-5/8" 36# casing will have special collars turned down to an outside diameter of 10-1/4" for clearance in a 12-1/4" hole. The turned down collars do not reduce collar strength rating. The new proposed casing and cement program will be:

17-1/2" hole with 13-3/8" 48# casing set at 350' with 400 sacks of cement, circulated To surface
12-1/4" hole with 9-5/8" 36# casing set at 1300' with 500 sacks of cement, circulated "
8-3/4" hole with 7" 23# & 26# casing set at 8800' with top of cement brought back to "
5000'

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Jan. 13, 2000

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY Tim W. Gum TITLE District Supervisor DATE 1-25-000

CONDITIONS OF APPROVAL, IF ANY: