

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-30910
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	
Haldeman EN	
8. Well No.	2
9. Pool name or Wildcat	Eagle Creek Atoka Morrow, East
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	
3421' GR	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:	OIL WELL <input type="checkbox"/>	GAS WELL <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>
2. Name of Operator	YATES PETROLEUM CORPORATION		
3. Address of Operator	105 South 4th St., Artesia, NM 88210		

4. Well Location	Unit Letter G : 1980 Feet From The North Line and 2310 Feet From The East Line
Section 31	Township 17S Range 26E NMFM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, conductor, resume drilling, surface casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rathole machine at 9:45 AM 6-27-2000. Drilled to 40'. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified Mike w/OCD-Artesia of spud. Resumed drilling a 17-1/2" hole with rotary tools at 6:00 AM 6-29-2000.

TD 356'. Reached TD at 5:30 PM 6-29-2000. Ran 8 joints of 13-3/8" 48# H-40 (361.18') of casing set at 358'. 1-Texas Pattern notched guide shoe set at 358'. Insert float set at 314'. Cemented with 450 sacks Class C Premium Plus and 2% CaCl2 (yield 1.34, weight 14.8). PD 9:15 PM 6-29-2000. Bumped plug to 230#, OK. Circulated 55 sacks. WOC. Cut off and welded on flow nipple. Drilled out at 4:15 PM 6-30-2000. WOC 19 hours. Reduced hole to 12-1/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Aug. 30, 2000

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use) ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR Bob

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

SEP 12 2000