

45F
012

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-30910
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Haldeman EN
8. Well No. 2
9. Pool name or Wildcat Eagle Creek Atoka Morrow, East

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION ✓
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter <u>G</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>2310</u> Feet From The <u>East</u> Line Section <u>31</u> Township <u>17S</u> Range <u>26E</u> NMFM <u>Eddy</u> County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3421' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Intermediate casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 1264'. Reached TD at 8:15 PM 7-1-2000. Ran 28 joints of 9-5/8" 36# J-55 (1264.26') of casing set at 1260'. 1-Texas Pattern notched guide shoe set at 1260'. Insert float set at 1219'. Cemented with 200 sacks Thixset, 1/4#/sack flocele and 350 sacks Halliburton Lite, 1/4#/sack flocele, 5#/sack salt and 5#/sack gilsonite (yield 2.01, weight 12.6). Tailed in with 200 sacks Class C Premium Plus and 2% CaCl2 (yield 1.34, weight 14.8). PD 5:45 AM 7-2-2000. Bumped plug to 794#, OK. Cement did not circulate. WOC 5 hours and ran Temperature Survey and found top of cement at 597'. Ran 1". Tagged cement at 580'. Pumped 200 sacks Class C and 2% CaCl2. PD 1:30 PM 7-2-2000. WOC 1 hour. Ran 1". Tagged cement at 455'. Pumped 150 sacks Class C and 2% CaCl2. PD 4:00 PM 7-2-2000. WOC 2 hours. Ran 1". Tagged cement at 426'. Spotted 50 sacks Class C and 3% CaCl2. PD 7:00 PM 7-2-2000. WOC 1 hour. Ran 1". Tagged cement at 426'. Spotted 50 sacks Class C and 4% CaCl2. PD 8:30 PM 7-2-2000. WOC 1 hour. Ran 1". Tagged cement at 364'. Spotted 50 sacks Class C and 4% CaCl2. PD 10:30 PM 7-2-2000. WOC 1 hour. Ran 1". Tagged cement at 364'. Spotted 50 sacks Class C and 4% CaCl2. PD 11:40 PM 7-2-2000. WOC 2 hours. Ran 1". Tagged cement

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CONTINUED ON NEXT PAGE:

SIGNATURE Rusty Klein TITLE Operations Technician DATE Aug. 30, 2000
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY

TITLE

DATE


CONDITIONS OF APPROVAL, IF ANY:

SEP 12 2000

YATES PETROLEUM CORPORATION
Haldeman EN Com #2
Section 31-T17S-R26E
Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:

at 252'. Spotted 100 sacks Class C Neat. PD 3:00 AM 7-3-2000. Circulated 21 sacks.
WOC. Nippled up and tested to 1000# for 30 minutes, OK. Drilled out at 9:45 PM 7-3-2000.
WOC 40 hours. Reduced hole to 8-3/4". Resumed drilling.

A handwritten signature in cursive script, appearing to read "Rusty Klein", written over a horizontal line.

Rusty Klein
Operations Technician
August 30, 2000