			CIST	-+-
ubmit 3 Copies Appropriate	State of New Me Energy, Minerals and Natural Re	xico sources Department	- AV	Form C-103 Revised 1-1-89
istrict Office I <u>STRICT I</u> O. Box 1980, Hobbs, NM 88240	OIL CONSERVATIO P.O. Box 208	N DIVISION	V WELL API NO. 30-015-	30949
ISTRICT II O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexico		5. Indicate Type of Lease	
ISTRICT III 00 Rio Brazos Rd., Aziec, NM 87410		189 5000 - 5	6. State Oil & Gas Lease	No.
DO NOT USE THIS FORM FOR PI	TICES AND REPORTS ON WEL ROPOSALS TO DRILL OR TO DEEPEN ERVOIR. USE "APPLICATION FOR PEI C-101) FOR SUCH PROPOSALS)	LBECENTERCK TO AN	7. Lease Name or Unit A	greement Name
Type of Well: OIL GAS WELL WELL	Х ОТНЕЯ	Sever the	Sadie	AUP
Name of Operator YATES PETROLEUM CORPO			8. Well No. 1	
3. Address of Operator 105 South 4th St., Artesia, NM 88210			9. Pool name or Wildcat Atoka Morrow, West	
Well Location	.650 Feet From The North	Line and990	Feet From The	East Line
	10. Elevation (Show whether	9' GR Nature of Notice, F	NMPM Edd Report, or Other Dat BSEQUENT REPO	 a
	PLUG AND ABANDON CHANGE PLANS	REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB		
] 	OTHER: Spud, conductor, resume drilling, X surface casing & cement		
	perations (Clearly state all pertinent details, o	and give pertinent dates, incl	luding estimated date of start	
Spudded a 26" hole w of 20" conductor pip Resumed drilling a 1	vith rat hole machine at be. Cemented to surface 17-1/2" hole with rotary	tools at 12:30	AM 3-1-2000.	
casing set at 400'. 354'. Cemented with 14.6). Tailed in with 3-1-2000. Bumped pl Temperature Survey a Spotted 35 sacks "C cement at 191'. Spo	D at 3:30 PM 3-1-2000. 1-Texas Pattern notcher h 200 sacks Thixad, 1% C ith 400 sacks "C" with 2 lug to 500 psi, OK. Cem and found top of cement " and 2% CaCl2. PD 3:40 otted 75 sacks Class C a ged cement at 158'. Spo ed to load hole with wat	a guide shoe set aCl2, 10#/sack g % CaCl2 (yield ent did not cir at 210'. Ran 1 AM 3-2-2000. nd 4% CaCl2. P tted 50 sacks " er and circulat	gilsonite (yield 1.34, weight 14. culate. WOC 6 h ". Taged cement WOC 1 hour. Ran D 4:45 AM 3-2-20 C" with 4% CaCl2 e. PD 6:30 AM 3	1.52, weight 8). PD 7:00 PM ours. Ran at 251'. 1". Tagged 000. WOC 1-1/2 2. Cement on 3-2-2000. PAGE:
<u>tubing at/96', fri</u>	THE THE SING CONTINCES OF THE DOOR OF THE STORE		Technician	=
I hereby certify that the information above	is the and complete to the best of my knowledge a	me Operations		DATE April 5, 2000
tubing at/96'. Tri. I hereby certify that the information above SHONATURE ULLER TYPE OR FRINT NAME RUSTY K1	1 Jun	nne Operations		DATE <u>April 5, 2000</u> TELEPHONE NO. 505/748-1

-+