

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-30949

5. Indicate Type of Lease STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Sadie AUP

8. Well No. 1

9. Pool name or Wildcat
Atoka Morrow, West

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3479' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter H : 1650 Feet From The North Line and 990 Feet From The East Line
Section 35 Township 17S Range 25E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Intermediate casing & cement <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 1302'. Reached TD at 5:00 AM 3-4-2000. Ran 29 joints of 9-5/8" 36# J-55 (1306') of casing set at 1302'. 1-Texas Pattern notched guide shoe set at 1301'. Insert float set at 1256'. Cemented with 200 sacks Thickset H, 10% A-10B, 1% CaCl2 and 10#/sack gilsonite (yield 1.52, weight 14.6) and 600 sacks "C" (65-35-6), 2% CaCl2 and 5#/sack gilsonite (yield 1.97, weight 12.5). Tailed in with 200 sacks "C" with 2% CaCl2 (yield 1.34, weight 14.8). PD 3:00 PM 3-4-2000. Bumped plug to 530 psi, OK. Cement did not circulate. WOC 6 hours and ran Temperature Survey. Found top of cement at 700'. Ran 1". Tagged cement at 633'. Spotted 50 sacks "C" with 4% CaCl2. PD 10:00 PM 3-4-2000. WOC 1 hour. Ran 1". Tagged cement at 265'. Spotted 50 sacks "C" with 4% CaCl2. PD 11:30 PM 3-4-2000. WOC 1 hour. Ran 1". Tagged cement at 443'. Spotted 50 sacks "C" with 2% CaCl2. PD 1:00 AM 3-5-2000. WOC 2 hours. Ran 1". Tagged cement at 441'. Spotted 75 sacks "C" with 4% CaCl2. PD 3:30 AM 3-5-2000. WOC 1-1/2 hour. Ran 1". Tagged cement at 405'. Spotted 75 sacks "C" with 4% CaCl2. PD 5:15 AM 3-5-2000. WOC 1-1/4 hour. Ran 1". Tagged cement at 242'. Spotted 105 sacks "C" with 2% CaCl2. Circ 30 sacks to pit. PD 7:00 AM 3-5-2000.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE April 5, 2000

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY SUPERVISOR, DISTRICT II TITLE DATE 4-11-00

CONDITIONS OF APPROVAL, IF ANY: