Submit 3 Copies to Appropriate District Office	State of New M Energy, Minerals and Natural I		as F	Form C-103 Revised 1-1-89
DISTRICT I P.O. Box 1980, Hobbs, NM 88240 <u>DISTRICT II</u> P.O. Drawer DD, Artesia, NM 88210 DISTRICT III	OIL CONSERVATI P.O. Box 20 Santa Fe, New Mexico)88	WELL API NO. 30-015-309 5. Indicate Type of Lease STAT	
1000 Rio Brazos Rd., Aztec, NM 8741	0 -	A	6. State Oil & Gas Lease No.	
(DO NOT USE THIS FORM FOR A DIFFERENT RES	DTICES AND REPORTS ON WE PROPOSALS TO DRILL OR TO DEEPER SERVOIR. USE "APPLICATION FOR PE C-101) FOR SUCH PROPOSALS.	TOR PLUG BACK TO A	7. Lease Name or Unit Agreen	veni Name
1. Type of Well: OIL GAS WELL WELL	<u>ত</u>			
2. Name of Operator	/	- S	Ernest AUQ 8. Well No.	
YATES PETROLEUM CORPO	DRATION V		1	
105 South 4th St., A	rtesia, NM 88210		9. Pool name or Wildcat Atoka-Morrow,	West
	80 Feet From The South	Line and990		st Line
Section 35 Township 17.S Range 25.E NMPM Eddy County 10. Lio. Elevation (Show whether DF, RKB, RT, GR, etc.) 3504' GR 3504' GR 10. 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING Interpretations (Charly abandon) Commence DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING CHARGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: OTHER: Surflace Casing & cement surflace casing & cement 12. Describe Proposed or Completed Operations (Clearly state all periveri details, and give periveri date: including estimated date of staring any proposed work) SEE RULE 1103. Spudded a 26" hole with rat hole machine at 9:30 AM 2-29-2000. Drilled to 40'. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified Mary Ann w/OCD-Artesia of spud. Resumed drilling a 17-1/2" hole with rotary tools at 10:45 PM 3-7-2000. NOTE: Notified Leslie w/OCD-Artesia answering service of resuming drilling. TD 399'. Reached TD at 6:45 AM 3-8-2000. Ran 9 joints of 13-3/8" 48# H-40 (404.42') of casing set at 399'. 1-Texas Pattern notched guide shoe set at 398'. Insert float set at 335'. Cemented with 400 sacks "C				
I hereby certify that the information above is to	up and complete to the best of my knowledge and i	xdiał.		
SKONATURE Custin	un m	• Operations Te	chnician DATE A	oril 3, 2000
TYPEOR PRINT NAME Rusty Klei	n		TELEPHON	ENO. 505/748-1471
(This space for State Use)	Sim W. Sum		SOR, DISTRICT II	4-6.00
CONDITIONS OF APPROVAL, IP ANY:	m.	E	DATE	<u> </u>