

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTSUBMIT IN TRIPLICATE
(Other instructions on
reverse side)FORM APPROVED
OMB NO. 1004-0136
Expires: February 28, 1995

APPLICATION FOR PERMIT TO DRILL OR DEEPEN

1a. TYPE OF WORK

DRILL ☒DEEPEN ☐

b. TYPE OF WELL

OIL
WELL ☐GAS
WELL ☒OTHER ☐SINGLE
ZONE ☒MULTIPLE
ZONE ☐

2. NAME OF OPERATOR

CONCHO RESOURCES, INC.

(JIM BLOUNT) 915-683-7443

3. ADDRESS AND TELEPHONE NO.

110 WEST LOUISIANA SUITE 410 MIDLAND, TEXAS 79702 (915-683-7443)

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

At surface

1650' FSL & 660' FEL SEC. 25 T16S-R27E EDDY CO. NM

At proposed prod. zone

SAME

Unit I

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE

Approximately 11 miles Northeast of Artesia New Mexico.

15. DISTANCE FROM PROPOSED

LOCATION TO NEAREST

PROPERTY OR LEASE LINE, FT.

(Also to nearest drilg. unit line, if any)

660'

18. NO. OF ACRES IN LEASE

320

17. NO. OF ACRES ASSIGNED

TO THIS WELL

320

19. PROPOSED DEPTH

9500'

20. ROTARY OR CABLE TOOLS

ROTARY

21. ELEVATIONS (Show whether DF, RT, GR, etc.)

3508' GR.

22. APPROX. DATE WORK WILL START
When Approved

PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	GRADE SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
25"	Conductor	NA	40'	Cement to surface with Redi-mix
17 1/2"	H-40 13 3/8"	48	375' 400'	450 Sx. Circulate to surface.
12 1/4"	J-55 8 5/8"	24	1800'	1000 Sx. " " "
7 7/8"	J-55, N-80 5 1/2"	15.5 & 17	9500'	1500 Sx. Use DV tool circulate

1. Drill 25" hole to 40'. Set 40' of 20" Conductor and cement to surface with Redi-mix.
2. Drill 17 1/2" hole to 400'. Run and set 400' of 13 3/8" H-40 48# ST&C casing. Cement with 450 Sx. of Class "C" cement + 2% CaCl, circulate cement to surface.
3. Drill 12 1/4" hole to 1800'. Run and set 1800' of 8 5/8" J-55 24# ST&C casing. Cement with 1000 Sx. of Class "C" cement + 1/2# flocele/Sx. + 2% CaCl, circulate cement to surface.
4. Drill 7 7/8" hole to 9500'. Run and set 9500' of 5 1/2" casing as follows: 1800' of 17# N-80 LT&C, 6000' of 15.5# J-55 LT&C, 1700' of 17# N-80 LT&C casing. Cement 1st stage with 900 Sx. of Class "H" Premium Plus + additives, 2nd stage with 600 Sx. of Class "C" + additives, circulate cement to surface.

Notify OCD at SPUD & TIME
to witness cementing the
13378" casing.

ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

SIGNED Joe T. Janice TITLE AgentDATE 01/04/00

(This space for Federal or State office use)

PERMIT NO. _____

APPROVAL DATE _____

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
CONDITIONS OF APPROVAL, IF ANY:APPROVED BY ROBERT L. BERRY TITLE Assistant Field Office Manager,
Lands and Minerals DATE _____

*See Instructions On Reverse Side

The 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

