

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division  
811 S. 1st Street  
Artesia, NM 88210-2834

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT-" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Gas Well ☒ Gas Well ☐ Other

2. Name of Operator

Chi Operating, Inc.

3. Address and Telephone No.

P.O. Box 1799 Midland, Texas 79702

4. Location of Well (Footage, T., R., M., or Survey Description)

Section 3 T17S, R28E  
1650' FNL & 660' FWL

5. Lease Designation and Serial No.

NM-012897

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ironsides Federal #1

9. API Well No.

30-015-31171

10. Field and Pool, or Exploratory Area

Crow Flat; Morrow SE Gas Pool

11. County or Parish, State

Eddy

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

**TYPE OF SUBMISSION**

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

**TYPE OF ACTION**

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other Completion  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded well on 6/07/00. Drilled 17 1/2" hole to 350'. Set 13 3/8"-54.5# @ 350' & cmtd w/300 sks lead, 100 sks of tail, circ 190 sks. Drld 11" hole to 2068'. Set 8 5/8" 24# @ 2068. Cmtd w/625 sks of lead & 200 sks tail. TOC @ 158'. Drld. 7 7/8" hole to 10023'. Set 5 1/2"-17#-N-80 @ 10,023. Cmtd w/900 sks.TOC @ 6090'. Released rig 6/28/00. Started completion 7/10/00. Cleaned out to PBTD of 9979'. CBL had TOC @ 6090'. Perf. 9640-44,9660-64',9702-12-4SPF. Fractured w/39,400 gals of foam & 39,850 lbs of 20/40 Interprop. Recover load & test.

ACCEPTED FOR RECORD

AUG 9 2000

BLM

14. I hereby certify that the foregoing is true and correct

Signed

Title

Engineer

Date

7/22/00

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instructions on Reverse Side