Submit 3 Copies To Appropriate District Office DISTRICT I 1625 N. French Dr., Hobbs, NM 88240 DISTRICT II 811 South First Artesia NM 88210

State of New Mexico Energy, Minerals and Natural Resources WELL API NO.

Form C-103 Revised March 25, 1999

OIL CONSERVATION DIVISION

30-015-31173

DISTRICT III	2040 South	h Pacheca 6789 70 5. Indicate Type of Lease STATE STATE FEE				
1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 2040 S. Pacheco, Santa Fe, NM 87505	Santa Fe, N	6. State Oil & Gas Lease No. B-2071				
SUNDRY NOTI (DO NOT USE THIS FORM FOR PRODIFFERENT RESERVOIR. USE "APPLI	CES AND REPORTS ON DPOSALS TO DRILL OR TO DEEPER CATION FOR PERMIT" (FORM C-10	LOR PLUGBACK HOYA	Lease Name or Unit Agreement Na	me:		
1. Type of Well: Oil Well ☐ Gas Well	X Other	300	Geronimo "27" State			
2. Name of Operator V Louis Dreyfus Natural Gas Corporation			8. Well No. 1			
3. Address of Operator 14000 Quail Springs Parkway, Suite 600 Oklahoma City, OK 73134			9. Pool name or Wildcat Empire Morrow South			
4. Well Location Unit letter O: 700	feet from the South	line and <u>1850</u>	feet from the <u>East</u> line			
Section 27	Township 17S	Range 28E	NMPM Eddy County			
	10. Elevation (Show whether 3668)	· DF, RKB, RT, GR, etc.)				
11. Check	Appropriate Box to Indica	ate Nature of Notice, Re	eport or Other Data			
*^ ^			OUENT REPORT OF:			
PERFORM REMEDIAL WORK TEMPORARILY ABANDON	PLUG AND ABANDON CHANGE PLANS	REMEDIAL WORK COMMENCE DRILLING	DPNS.			
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST AND CEMI		_		
OTHER:		OTHER:				
12. Describe proposed or completed op posed work). SEE RULE 1103. F	perations. (Clearly state all pertines or Multiple Completions: Attach w	nt details, and give pertinent da rellbore diagram of proposed co	ates, including estimated date of starting completion or recompilation.	any pro-		
Spud 6/18/00. 6/18/00 ran 13 3. + 2% CaCl. Displaced w/66 bbl WOC 18 hours commenced drlg	s water, bumped plug, float did	emented w/225 sks H/L + 2 not hold. SI, WOC, circula	% CaCl, tail w/200 sks P ated 75 sxs cement to reserve.			

6/23/00 ran 62 jts of 9 5/8" csg, 36# K55, set @ 2649.48'. Cement as follows: Lead = 600 sks Interfill "C" neat, tail w/250 sks PremPlus w/2% CaC1. Plug down @ 11:07 PM, circ 123 sks cement to reserve, float held. WOC 20 hrs. 6/24/00 commenced drilling.

I hereby certify that the information above is true and com	plete to the bes	st of my knowledge and belie	f.	
SIGNATURE COMP Christian		Regulatory Technician		E
Type or print name Carla Christian			Telephone No. (40	5) 749-5263
(This space for State use)		0.+-4-		

Sim W. Gump TITLE Kestrut Supervisor

DATE WUL 12 200

APPROVED BY Conditions of approval, if any: