



7/24/2000

RIO OCHO STATE 26 #1

7/24/2000 Days- 5; Depth- 1625; FTG- 450; DRILLING; Anhy, Lime, Salt; DRILLING; MW- 10; Vis- 28; pH- 9; Chls- 182K; Calc- 1980; Liner- 6; Stroke- 8; SPM- 101; Press- 1150; GPM- 300; DEV- 1 deg 15' @ 1405; 1 deg 45' @ 1530; Bit#- 2; SN- K20DM; Size- 12 1/4(RT); Mfg- HTC; Type- ATJ-33C; Jets- 12/12/12; In- 403; Ftg- 1222; Hrs- 59 3/4; Ft/Hr- 20.451; WOB- 50/55; RPM- 70; BHA(ft)- 615.61; 1 Bit, S/S, 1-8" DC, RMR, 8-8" DCs= 284; 5 hrs- Drill from 1175'-1322' (147'). 1/4 hr-Service rig. 6 1/4 hrs- Drill from 1370'-1447' (77'). 1/4 hr-WLS @ 1405 (1 deg 15'). 7 1/2 hrs-Drill from 1447'-1574' (67'). 1/2 hr-WLS @ 1530' (1 deg 45'). 4 1/4 hrs-Drill from 1574'-1625' (51'). Note: Had to repair pit lining, high winds got under seam tore all of one side of inner reserve, pit too large to maintain high fluid level & keep expense down.

TMC-\$ 1,249 TDC-\$ 8,662 CWC-\$ 100,551 CMIC- MH