

State of New Mexico
State License 6 Copies
Fee License 5 Copies
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Revised March 25, 1999

Well API No.

30-015-31189

5. Indicate Type of Lease

State ☐ Fee ☐

State Oil & Gas Lease No.

Well Completion or Recompletion Report and Log

1a. Type of Well: ☐ Oil Well ☒ Gas Well ☐ Dry ☐ Other

b. Type of Completion

☐ New Well ☐ Work over ☐ Plug Back ☐ Diff. Resvr. ☒ Other DHC

2. Name of Operator

Devon SFS Operating, Inc.

3 Address of Operator

20 North Broadway, Ste 1500, Oklahoma City

7. Lease Name or Unit Agreement Name

Veranda 16 State Com

8. WELL NO.

9. Pool name or Wildcat
Kennedy Farms Upper Penn, W. Kennedy Farms
Farms Morrow

4. Well Location

Unit Letter O : 660' Feet From the South Line and 1980' Feet From the East Line
Section 16 17S Township 26E Range NMPM Eddy County

10. Spudded Spud 2/21/2001	11. Date T.D. Reached 3/15/2001	12. Date Compl. (Ready to Prod) Commingle 6/17/02	13. Elevations(DF&RKB,RT,GR, etc) 3389' GR	14. Elev. Casinghead
15. Total Depth 8600'	16. Plug Back T.D. 8508'	17. IF Multiple Compl. How Many Zones 3	18. Intervals Drilled by Rotary	Cable Tools
19. Producing Intervals(s), of this completion - Top, Bottom, Name 7628' - 8399'			20. Was Directional Survey Made	
21. Type Electric and Other Logs Run Logs sent with Original completion			22. Was Well Cored No	

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	Amount Pulled
13 3/8"	48#, H-40	350'	17 1/2"	435 sx 85 sx circ	
8 5/8"	32#, J-55	1424'	12 1/4"	800sx TOC 200'	
5 1/2"	15, 17, J-55, L-80	8597'	7 7/8"	830sx TOP 6000'	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT

25. TUBING RECORD

SCREEN	SIZE	DEPTH SET	PACKER SET
	2 7/8"	8357'	

26. Perforation record (interval, size, and number)

Morrow 8366' - 8393'
Strawn - 7938' - 7980 4 SPF total 104 holes
Lower Canyon 7628' - 7781' 4 SPF Total 44 holes

Cisco 6628' - 6825' Total 31 holes Squeezed w/136 sx in perfs

27. Acid, shot, fracture, cement, squeeze, etc.

Depth Interval	Amount and Kind material used
8366' - 8393'	15 gal 7 1/2% HCL acid
7938' - 7980'	4000 gal 15% HCL
7628' - 7781'	2000 gal 15% HCL
6628' - 6825'	5000 gal 15% HCL

28. PRODUCTION

Date First Production 6/18/2002		Production Method (Flowing, gas lift, pumping - Size and type pump) Flowing			Well Status Prod. Or Shut In) Producing		
Date of Test 6/22/2002	Hours Tested 24HRS	Choke Size 0.8	Prod'n For Test Period	Oil - bbl 0	Gas - MCF 229	Water - Bbl. 0	Gas - Oil Ratio
Flow Tubing Press.	Casing Pressure	Calculate 24-Hour Rate	Oil - Bbl. 0	Gas - MCF 229	Water - Bbl. 0	Oil Gravity - API - (Corr.)	
28 Disposition of Gas (Sold, used for fuel, vented etc.) SOLD					Test Witnessed By		

30 List Attachments

31 I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief

Signature Karen Cotton Printed Karen Cotton
Name Engineering Technician

Date 6/24/02

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem test. All depths reported shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filled in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy		T. Canyon	7282'
T. Salt		T. Strawn	7827'
B. Salt		T. Aloka	8144'
T. Yates		T. Miss	Barnett Shale 8440'
T. 7 Rives		T. Devonian	
T. Queen		T. Silurian	
T. Graybury		T. Montoya	
T. San Andres	940'	T. Simpson	
T. Glorieta	2352'	T. McKee	
T. Paddock		T. Ellenburger	
T. Blinberry		T. Gr. Wash	
T. Tubb	3684'	T. Delaware Sand	
T. Drinkard		T. Bone Springs	
T. Abo Shale	4340'	T. Morrow	8250'
T. Wolfcamp	5440'	T. Morrow Clastics	8318'
T. Perm		T. Morrow Sand	8366'
T. Claoo (Bought C)	6596'	T. Miss Chester	8520'
		TD	9600'

Northwestern New Mexico

T. Ojo Alamo		T. Penn "B"	
T. Kirtland-Fruitland		T. Penn "C"	
T. Pictured Cliffs		T. Penn "D"	
T. Cliff House		T. Leadville	
T. Menefee		T. Madison	
T. Point Lookout		T. Elbert	
T. Mancos		T. McCracken	
T. Gallup		T. Ignacio Ozate	
Base Greenhorn		T. Granite	
T. Dakota			
T. Morrison			
T. Todillo			
T. Entrada			
T. Wingate			
T. Chinle			
T. Permian			
T. Penn "A"			

OIL OR GAS
SANDS OR ZONES

NO. 1, from	to	NO. 3, from	to
NO. 2, from	to	NO. 4, from	to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole

NO. 1, from	to	feet
NO. 2, from	to	feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology