INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all specific tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Canvon

T. Anhy _

Northwestern New Mexico

I. Ann	У	T	. Canyon	<u>77</u> 19.	0 T. Ojo	Alamo	т	Penn	"B"
T. Salt T B. Salt T		. Strawn	8112.	2.0 T. Kirtland-Fruitland			T Penn "C"		
1. Yates T		Miss 9086.0 T. Cliff House Devonian T. Menefee Silurian T. Point Lookout				T.	T. Leadville		
1. 7 Rivers T		. Devonian		T. Menefee			T. Madison		
1. Queen 460.0 T		. Silurian		T. Point Lookout		out T.	T. Elbert		
T. Grayburg T T. San Andres 1232.0 T		. Montoya		_ T. Mar	T. Mancos		T. McCracken		
T. San Andres <u>1232.0</u> T. T. Glorieta <u>2625.0</u> T. T. Paddock T		Simpson		_ T. Gal	Г. Gallup 7		Γ. Ignacio Otzte		
Glorieta <u>2625.0</u> T		. McKee		_ Base (Base Greenhorn		. Granite		
T. Abo 4702.0 T		Bone Springs	_ T. Entr	. Entrada T					
1. ADO $4/02.0$ T. Wolfcomp 6072.0 T.		Bone Springs T. Entrada T. Wingate T. Chinle				T.			
						nam			
T. CISC	O (Bough	n C) <u>7108.0</u> [.			_ T. Pen	n. "A" _	T.		
			OIL OR GA						
No. 1,		to		No. 3, from				to	
No. 2, from to			No. 4, fro			4, from		to	
المرمان والم			IMPOR	TANT	WATER		S		
include	aata ol	n rate of water	inflow and eleval	ion to	which w	ater ros	e in hole.		
No. 1, 1			to feet						
No. 2, from			to feet						
No. 3, 1	rom		to			fe	eet		
		LITHOLO	OGY RECOR	D (At	tach add	itional s	heet if necessa	ary)	
From	То	Thickness in Feet	Lithology		From	То	Thickness in Feet		Lithology
460.0	2625.0		dolo,anhy						
2625.0	2800.0		sand,dolo						
2800.0	4030.0		dolo,anhy						
4030.0	4250.0		sand						
4250.0	6072.0		dolo,anhy						
6072.0			lime,shale						
7108.0	7719.0		lime,shale						
7719.0 8580.0	8580.0 8700.0		limestone						
8700.0	8830.0		shale,lime						
8830.0	9190.0		lime shale,sand						
0000.0	0100.0		Shale, Saliu						