## Submit 3 Copies to Appropriate District Office

## State of New Mexico Energy, ...nerals and Natural Resources Department

015/	Form C-103 Revised 1-1-89
U	

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

OIL CONSERVATION DIVISION

P.O. Box 2088 Santa Fe, New Mexico 87504-2088

25911

	~ /·
WE	LL API NO.
	30-015-31315
5.	Indicate Type of Lease STATE X FEE
6.	State Oil & Gas Lease No. B-8617
77	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,

DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410	6. State Oil & Gas Lease No. B-8617					
SUNDRY NOTICES AND REPORTS ON WE (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFERENT RESERVOIR. USE "APPLICATION FOR POPOSALS.)	N OH PLUG BACK (OA 7. Lease Name or Unit Agreement Name					
1. Type of Well:  Of. GAS WELL X OTHER	181 - 191 6 3 1 3 1 3 1 3 1 3 1 3 1 3 1 3 1 3 1					
2. Name of Operator	8. Weil No.					
Yates Drilling Company	#2					
3. Address of Operator	9. Pool name or Wildcat					
105 South 4th Street, Artesia, NM 88210	Empire Penn					
4. Well Location  Unit Letter L : 1980 Feet From The South  Section 15 Township 178  (Show wheth	Line and 660 Feet From The West Line  Range 28E NMPM Eddy County  ther DF, RKB, RT, GR, etc.)					
(1////////////////////////////////////						
11. Check Appropriate Box to Indicate NOTICE OF INTENTION TO:	subsequent Report, or Other Data SUBSEQUENT REPORT OF:					
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK ALTERING CASING					
TEMPORARILY ABANDON CHANGE PLANS	COMMENCE DRILLING OPNS. X PLUG AND ABANDONMENT					
PULL OR ALTER CASING	CASING TEST AND CEMENT JOB X					
OTHER:	OTHER: SPUD X					
12. Describe Proposed or Completed Operations (Clearly state all pertinent detail work) SEE RULE 1103.  Spuid well at 1:30 pm. 10-19-00.	ls, and give pertinent dates, including estimated date of starting any proposed					

10-22-00 TD 398'. Ran 9 joints 13 3/8", 48# casing, set at 398'. Texas Pattern Notched Guide shoe set at 398'. Insert float set at 357.57'. Cemented with 163 sxs. 35:65:6, Class "C" cement + 2% CaCl2 (yld 1.97, wt 12.5). Tailed in with 200 sxs. C neat with 2% CaCl2 (yld 1.34, wt 14.8). Plug down at 4:07 pm, 10-21-00. Bumped plug to 500 psi. Float held okay. Circulated 99 sxs. to pit. WOC 18 hrs. Resumed drilling at 10:00 am, 10-22-00.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.  SIGNATURE	(This space for State Use)	BO		DEC 0 4 2000
SIGNATURE Karen Lushmai me Engineering Technician DATE 11-15-00	TYPE OR PRINT NAME			
Kare Lushner Engineering Technician DATE 11-15-00	SIGNATURE ————————————————————————————————————	\		TELEPHONE NO.
	SIGNATIONE & aren & Lushman		me Engineering Technician	DATE
	I hereby cerufy that the information above is true and complete to the be			11-15-00
			<del>!</del>	

ORIGINAL SIGNED BY TIM W. GUM DISTRICT H SUPERVISOR

UEL U 4 ZUUL

APPROVED BY -