

EXHIBIT D
AUXILIARY EQUIPMENT
SANTA FE SNYDER CORP.
Riverside "31" Fed Com. #1
Section 31, T-16-S, R-27-E
Eddy County, New Mexico

DRAWWORKS	BDW 650M 650 HP, with Parmac Hydromatic brake
ENGINES	Two Caterpillar D-353 diesels rated at 425 HP each
ROTARY	Ideco 23", 300 ton capacity
MAST/SUB	Ideal 132', 550,000 lb rated static hook load with 10 lines. Wagner 15' high substructure
TRAVELLING EQUIPMENT	Gardner-Denver, 300 ton, 5 sheave w/BJ 250 ton hook. Brewster Model 7 SX 300 ton swivel
PUMPS	Continental-EMSCO DC-700 and DB-550, 5-12 x 16" Duplex, Compound driven
PIT SYSTEM	1-Shale Pit 6X7X35', 1-Setting Pit 6X7X38', 1-Suction Pit 6X7X34' w/5 mud agitators. Two centrifugal mud mixing pumps and a Double Screen Shale Shaker.
LIGHT PLANT	Two CAT 3306 diesel electric sets 180 KW prime power
BOP EQUIP	13-5/8" 3000 psi WP double ram and 13-5/8" 3000 psi WP Shaffer Annular Preventer. Choke manifold rated at 3000 psi. Valvcon 5-station 80 gallon closing unit