

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco
Santa Fe, NM 87505

Form C-107
Revised March 25, 1996

WELL API NO.

30-015-31599

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

OXY Euphonium

8. Well No.

192463 #1

9. Pool name or Wildcat

Undsg. Cisco Canyon

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

OXY USA WTP Limited Partnership

3. Address of Operator

P.O. Box 50250 Midland, TX 79710-0250

4. Well Location

Unit Letter 4 : 660 feet from the south line and 660 feet from the west line

Section 19 Township 17S Range 26E NMPM County Eddy

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3436'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

TD-8435' PERFS-6490-6706'-8186-8220' Pkr @ 8125'
CASING: 13-3/8" 48# @ 420', 17-1/2", cmt w/360sx, TOC-Circ
8-5/8" 32# @ 1303', 12-1/4", cmt w/1135sx, TOC-Circ
4-1/2" 11.6# @ 8433', 7-7/8", cmt w/900sx, TOC-4540'-CBL

1. M&P 25sx cmt @ 8125-7875'-WOC/TAG
2. M&P 25sx cmt @ 7300-7050'
3. CIBP @ 6450', M&P 25sx cmt @ 6450-6200'-WOC/TAG
4. Cut & pull 4-1/2" csg at approximately 4540'
5. M&P 30sx cmt @ 4590-4490'-WOC/TAG
6. M&P 45sx cmt @ 3600-3500' 4000' - 4100' ← 100' p/u, 2070' - 2170'
7. M&P 40sx cmt @ 1353-1253'-WOC/TAG
8. M&P 35sx cmt @ 470-370' - TAG
9. M&P 20sx cmt Surface 10#MLF between plugs

Notify OCD 24 hrs. prior to any work done

Salt gel mud consisting of 10#
Brine W/25# of gel per bbl
must be placed between each plug

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David Stewart TITLE Sr. Regulatory Analyst DATE 7/1/02

Type or print name David Stewart

Telephone No. 915-685-5717

(This space for State use)

APPROVED BY [Signature] TITLE David Stewart DATE JUL 9 2002

Conditions of approval, if any:

OXY USA WTP LP
OXY EUPHONIUM #1
SEC 19 T17S R26E EDDY NM

