

Well name:

**West Red Lake Area**Operator: **Devon Energy Corporation**String type: **Production**Location: **Eddy County, NM****Design parameters:****Collapse**Mud weight: 9.630 ppg  
Design is based on evacuated pipe.**Minimum design factors:****Collapse:**

Design factor 1.125

**Burst:**

Design factor 1.00

**Environment:**H2S considered? No  
Surface temperature: 75 °F  
Bottom hole temperature: 95 °F  
Temperature gradient: 0.50 °F/100ft  
Minimum section length: 1,500 ft**Burst**Max anticipated surface  
pressure: 2,001 psi  
Internal gradient: 0.000 psi/ft  
Calculated BHP 2,001 psi

No backup mud specified.

**Tension:**8 Round STC: 1.80 (J)  
8 Round LTC: 1.80 (J)  
Buttress: 1.60 (J)  
Premium: 1.50 (J)  
Body yield: 1.50 (B)

Non-directional string.

Tension is based on buoyed weight.  
Neutral point: 3,417 ft

Run Seq	Segment Length (ft)	Size (in)	Nominal Weight (lbs/ft)	Grade	End Finish	True Vert Depth (ft)	Measured Depth (ft)	Drift Diameter (in)	Internal Capacity (ft³)
1	4000	5.5	15.50	J-55	LT&C	4000	4000	4.825	125.4
Run Seq	Collapse Load (psi)	Collapse Strength (psi)	Collapse Design Factor	Burst Load (psi)	Burst Strength (psi)	Burst Design Factor	Tension Load (Kips)	Tension Strength (Kips)	Tension Design Factor
1	2001	4040	2.02	2001	4810	2.40	53	217	4.10 J

Prepared by: **Jim Linville  
Devon Energy**Phone: (405) 228-4621  
FAX: (405) 552-4621Date: **March 12, 2001**  
**Oklahoma City, Oklahoma****Remarks:**

Collapse is based on a vertical depth of 4000 ft, a mud weight of 9.63 ppg. The casing is considered to be evacuated for collapse purposes. Collapse strength is based on the Westcott, Dunlop &amp; Kemler method of biaxial correction for tension.

Burst strength is not adjusted for tension.

Engineering responsibility for use of this design will be that of the purchaser.

RECEIVED  
2001 MAR 15 AM 9:28  
BUREAU OF LAND MGMT.  
ROSWELL OFFICE