

District I
1625 N. French Dr., Hobbs, NM 88240

District II
811 South First, Artesia, NM 88210

District III
1000 Rio Brazos Rd., Aztec, NM 87410

District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural Resources

Form C-101
Revised March 12, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Submit to Appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUG BACK OR ADD A ZONE

¹ Operator Name and Address Louis Dreyfus Natural Gas Corp. 14000 Quail Springs Parkway - Suite 600 Oklahoma City, OK 73134		² OGRID Number 25773
⁴ Property Code 28149		³ API Number 30-0 15-3/829
⁵ Property Name Geronimo "28" State Com		⁶ Well No. 1

⁷ Surface Location									
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
J	28	17S	28E		1500	South	1800	East	Eddy

⁸ Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
⁹ Proposed Pool 1 Empire: Marathon Penn.					¹⁰ Proposed Pool 2				

¹¹ Work Type Code N	¹² Well Type Code G	¹³ Cable/Rotary Rotary	¹⁴ Lease Type Code S	¹⁵ Ground Level Elevation 3684'
¹⁶ Multiple N	¹⁷ Proposed Depth 10,550	¹⁸ Formation Morrow	¹⁹ Contractor Patterson	²⁰ Spud Date 6/18/01

²¹ Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
17 1/2"	13 3/8"	48#	440'	450 sks	Surface
12 1/4"	9 5/8"	36#	2,700'	900 sks	Surface
7 7/8"	5 1/2"	17#	10,550	1300 sks	Tie back to
					9 5/8"

²² Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

1. Drill 17 1/2" hole to \pm 440'. Run 13 3/8" csg. and cement to surface w/450 sks cement.
2. Drill 12 1/4" hole to \pm 2,700'. Run 9 5/8" csg. and cement to surface w/900 sks cement.
3. Drill 7 7/8 " hole to \pm 10,550'. Run 5 1/2" csg. and cement to 9 5/8" w/1300 sks cement.
(A D.V. tool may be used to bring cement inside 9 5/8")

See attached "Exhibit 6" for BOP assembly.

²³ I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature: *Carla Christian*
Printed name: Carla Christian

Title: Regulatory Technician

Date: 6/11/01 Phone: 405-749-5263

OIL CONSERVATION DIVISION

Approved by: **ORIGINAL SIGNED BY TIM W. GUM**
Title: **DISTRICT II SUPERVISOR**

Approval Date: **JUN 18 2001** Expiration Date: **JUN 18 2002**

Condition of Approval:
Attached ☐