Form 3160-5 (June 1990)

Approved by

Conditions of approval, if any:

## UN D STATES DEPARTMENT OF THE INTERIOR

N.M. DIV-Dist. 2

1301 W. Grand Avenue APPROVED **BUREAU OF LAND MANAGEMENT** Artesia, NM 8821 Opires March 31, 1993
5. Deage Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation Type of Well ☐ Oil Well ⊠ Gas Well Other 8. Well Name and No. 2. Name of Operator **DEVON SFS OPERATING, INC.** Crow Flat 20 Fed Com #2 3. Address and Telephone No. 9. API Well No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611 30-015-31921 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) Crow Flat (Morrow) 1310' FNL & 1730 FWL, Sect 20, T16S-R28E, Unit C 11. County or Parish, State Eddy, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Water Shut-Off Casing Repair Final Abandonment Notice Altering Casing Conversion to Injection Dispose Water Other Spud Sundry (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* 9/15/01 – Spudded 17 ½" hole. BLM (Don Early) was notified. Drilled to 490'. 9/16/01 – Drilled to 505', set 13 3/8" 48#, H-40, ST&C csg @ 505', RU BJ Services & cmt'd w/200sx Class H, 250sx of 35:65:6 Poz, Tailed w/250 sx Class C, tagged cmt @ 54' from floor, Witnessed by Don Early w/BLM, topped out cmt with 10 yrs of 5 sx ready mix. 9/19/01 - Drilled 12 1/4" hole to 2010, set 8 5/8", 32#, J-55, LT&C, RU BJ Services & cmt'd w/Lead 560 sx 35:65 Poz Class C, tailed w/250 sx Class C, circulated 86 sx to the pits, 10/8/01 - Drilled 7 7/8" hole to 9900' TD'd hole on 10/8/01 circulated & conditioned hole for logs. 10/11/01 - Set 5 1/2", L-80, & J-55, 17# LT&C csg, cmt'd 5 1/2" csg w/1000 sx Class H7 released rig @ 04:00, 10/12/01 14. I hereby certify that the foregoing is true and correct Karen A. Cottom Date August 20, 2001 Engineering Technician (This space for Federal or State office use)

Title