

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Minerals and Natural Resources

Form C-103
Revised March 25, 1999

WELL API NO.
30-015-32388

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
V 5344

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
MURCHISON OIL & GAS, INC.

3. Address of Operator
1100 MIRA VISTA BLVD. PLANO, TX. 75093-4698

4. Well Location
Unit Letter **N** : **810** feet from the **SOUTH** line and **1980** feet from the **WEST** line
Section **1** Township **17S** Range **28E** NMPM **EDDY** County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPLETION <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Drill 8-1/2" hole to 10350'. Run open hole logs. Run casing as follows:

Float Shoe	1'
2 Jts 5-1/2" 17#/FT P-110 LTC	79'
Float Collar	2'
32 Jts 5-1/2" 17 #/FT P-110 LTC	1321'
13 Jts 5-1/2" 17 #/FT S-95 LTC	572'
238 Jts 5-1/2" 17 #/FT N-80 LTC	8405'
	10380'

Set casing @ 10350'. Cement with 1700 SXS 50:50 Class H + 5% Salt + 5/10% FL 52 & 25. Bump plug and floats held. Nipple down BOP and set slips. Release rig @ 0600 11/9/02.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Michael S. Daugherty TITLE VICE PRESIDENT OPERATIONS DATE 11/12/02
(972)

Type or print name MICHAEL S. DAUGHERTY Telephone No. 931-0700
(This space for State use)

APPROVED BY For record only TITLE _____ DATE _____
Conditions of approval, if any:

NOV 19 2002