

RECORD OF DRILL-STEM AND SPECIAL TESTS.

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from.....feet to.....feet, and from.....feet to.....feet.
 Cable tools were used from.....0.....feet to.....2383.....feet, and from.....feet to.....feet.

PRODUCTION

Put to Producing.....6-1-57....., 19.....

OIL WELL: The production during the first 24 hours was.....75.....barrels of liquid of which.....100.....% was
 was oil;% was emulsion;% water; and.....% was sediment. A.P.I.
 Gravity.....

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of
 liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico				Northwestern New Mexico			
T. Anhy.....	T. Devonian.....	T. Ojo Alamo.....		T. Kirtland-Fruitland.....			
T. Salt.....	T. Silurian.....	T. Farmington.....		T. Pictured Cliffs.....			
B. Salt.....	T. Montoya.....	T. Menace.....		T. Point Lookout.....			
T. Yates.....	T. Simpson.....	T. Mancos.....		T. Dakota.....			
T. 7 Rivers.....	T. McKee.....	T. Morrison.....		T. Penn.....			
T. Queen.....	T. Ellenburger.....	T.		T.			
T. Grayburg.....	T. Gr. Wash.....	T.		T.			
T. San Andres.....	T. Granite.....	T.		T.			
T. Glorieta.....	T.	T.		T.			
T. Drinkard.....	T.	T.		T.			
T. Tubbs.....	T.	T.		T.			
T. Abo.....	T.	T.		T.			
T. Penn.....	T.	T.		T.			
T. Miss.....	T.	T.		T.			

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0m	8	8	Sand & caliche	1640	1667	27	Red sand
8	30	22	Shale & caliche	1667	1715	48	Anhydrite
30	35	5	Shale	1715	1745	30	Anhydrite & lime
35	50	15	Red bed & gyp	1745	1770	25	Anhydrite
50	65	15	Gray rock	1770	1795	25	Gray lime
65	95	30	Gyp & anhydrite	1795	1815	20	Anhydrite & red rock
95	104	9	Red bed	1815	1853	38	Anhydrite
104	120	16	Gyp	1853	1865	12	Sand
120	215	95	Red bed	1865	2020	155	Anhydrite & red rock
215	310	95	Broken Anhydrite & salt	2020	2055	35	Anhydrite
310	325	15	Anhydrite	2055	2225	170	Lime
325	675	350	Salt	2225	2275	50	Sandy lime
675	970	295	Anhydrite & red rock	2275	2300	25	Broken lime
970	1120	150	Anhydrite	2300	2315	15	Sandy gray lime
1120	1150	30	Anhydrite & sand	2315	2355	40	Gray lime
1150	1365	215	Anhydrite	2355	2365	10	Sand
1365	1405	40	Anhydrite & red rock	2365	2380	15	Broken lime
1405	1430	25	Anhy & sandy red rock	2380	2383	3	White lime
1430	1640	210	Anhydrite	2383	TD		

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator.....Kinsaid & Watson.....Address.....Box 534, Artesia, N. M.....
 Name.....G. Rex Holmes.....Position or Title.....Agent.....