

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOCATE WELL CORRECTLY

The summary on this page is for the condition of the well at above date.

Commenced drilling June 12, 1956, 1956 Finished drilling June 24, 1956

OIL OR GAS SANDS OR ZONES

(Denote gas by $\mathbb{G}$)

No. 1, from 1961 to 1968 No. 4, from _____ to _____
 No. 2, from _____ to _____ No. 5, from _____ to _____
 No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____

No. 2, from _____ to _____

No. 3, from _____ to _____

No. 4, from _____ to _____

CASING RECORD

[illegible]

MUDDING AND CEMENTING RECORD

Size casting	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
8 5/8"	293'	50	Denton		
4 1/2"	1102'	100	Denton		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth set _____
Adapters—Material _____ Size _____

SHOOTING RECORD

[illegible]

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

DATES

-----, 19-----	Put to producing -----, 19-----
The production for the first 24 hours was -----	barrels of fluid of which -----% was oil; -----%
emulsion; -----% water; and -----% sediment.	Gravity, °Bé. -----
If gas well, cu. ft. per 24 hours -----	Gallons gasoline per 1,000 cu. ft. of gas -----
Rock pressure, lbs. per sq. in. -----	

EMPLOYEES

Horace Day	, Driller	Elmer Mahan	, Driller
J. D. Foster	, Driller		, Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	80	80	Surface and Rock
80	280	200	Blind Hole
280	310	30	Red Sand
310	725	415	Salt
725	1041	316 1041-280	Anky.
1041	1061	20	Anky-Lime
1061	1066	5	Oil Sand
1066	1080	14	Lime- Red Sand
1080	1101 TD	<u>21</u>	Anky.
		1101	

