

|  |  |  |
|--|--|--|
|  |  |  |
|  |  |  |
|  |  |  |

County Eddy Depth 3400' Pool Undesignated\* *(Brayburg)*

SCOUT REPORT  
NEW MEXICO OIL CONSERVATION COMMISSION

Company Nix & Curtis Well No. 1 Lease Continental-State

660 Feet from S. Line 1980 Feet from W. Line, Sec. 15 Twp. 17S Rge. 29E

Land State Contractor Roach & Shepard *CT*

T. A  
T. X  
B. X 715  
T. Del Li  
T. Del Sd  
T. Y  
T. SR  
T. Q 1775  
T. PR  
T. GB  
T. SA 2445  
T. Glo  
T. Blby  
T. CF

Elevation 3565 Spudded 2-1-56 Completed 9-7-56

T. Tu Total Depth 3253 li P. B. 2765  
T. Full Top Pay 2390 District 6  
T. DR I.P. F 46 BOPD  
T. Wich A. Base on BO 24 Hrs.  
T. Abo Choke: Intermittent Inch  
T. WC Tubing @ Ft.  
T. Hu Press: Tbg. Csg.  
T. Per-Pe GOR Gravity 35  
T. Penn Effective Perfs.:  
T. Strawn 20h 2390-95, 30h 2400-05, 40h 2654-64  
T. Miss 16h 2717-21, 16h 2723-27  
T. WF 32h 2732-40

CSG. & CEMENTING RECORD

| Size   | Feet         | Sax Cement   |
|--------|--------------|--------------|
| 10 3/4 | 150          | set          |
| 8 1/8  | 446          | 50 ✓         |
| 5 1/2  | 3169<br>3175 | 200<br>150 ✓ |

T. Dev Acid, Frac & Shooting Record:  
T. Sil 6000 R/A From 2654 To 64  
T. Fuss 10000 SOK From 2390 To 2405  
T. Mon 10,000 SOK From 2717 To 2740  
T. Simp From To  
T. McK  
T. Ell  
T. G.W.  
T. Gr

SHOWS

SS/O 1050  
S/O 2300 Bail 390 Wt + 890 lbm  
SS/g 2650  
S/  
S/  
S/

ILLEGIBLE

|        |                                   |                        |
|--------|-----------------------------------|------------------------|
| 2-8-56 | Drilg. 150' gravel, Water 140-145 | <i>3060 li</i>         |
|        | <i>951 anhyd</i>                  | APR 1 TD 3253 ✓ d plug |
|        | <i>1745 ✓</i>                     | @ 11 Bail 390 ft       |
|        | <i>2325 li</i>                    | TD 3253 li, fag        |
|        | <i>2573 ✓</i>                     | to 1000 R/A OH         |
|        | <i>TD 2669 d fag.</i>             | 3169-3253 fag          |
|        | <i>2760 li</i>                    | 38,000 + 27100 " OH    |
|        | Bail 2650-55 5g PH                | ✓✓✓✓✓                  |

TD 3253 li flowing sand + XW  
20 B XW 3 B blood oil PD  
✓✓

June 22 TD 3253 li flowing sand + XW  
150 BLO TAPES  
✓✓✓✓✓

Aug 8 TD 3253 li PB 2685 2 out BP 2655  
set BP 2765 perf 16h 2717-21, 16h 2723-27  
32h 2732-40  $\frac{1}{2}$  250 M/A frac 10,000 + 13,000  
set BP 2685 Perf 40h 2654-64 treat 6,000 B/L  
rec load sub 4 B O B/Hair for 4'  
TD 3253 li BP 2765 test lower zone  
do BP @ 2685 set PB @ 2700 sub 2760 8'  
TD 3253 li PB 2765 test sub 23480  
extra X with 1'  
TD 3253 li PB 2765 run the set BP 242;  
Perf 20h 2390-95 30h 2400-2405 frac  
10,000 + 15000" all perf  
TD 3253 li: PB 2765 NO Pat  
H/O 48 B NO 24'