

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
Marbob Energy Corporation

3. ADDRESS OF OPERATOR
P.O. Dr. 217, Artesia, N.M. 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: *660 FSL 1944 FEL*

AT TOP PROD. INTERVAL: *Same*

AT TOTAL DEPTH: *Same*

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) *Re-entry* ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

FEB 11 1983

O. C. D.
ARTESIA, OFFICE

5. LEASE

LC 028731-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

M. Dodd "A"

9. WELL NO.

21-Y

10. FIELD OR WILDCAT NAME

Grby Jackson On SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 15-T17S-R29E

12. COUNTY OR PARISH 13. STATE

Eddy N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3572' GR

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in reverse unit, dug out cellar, cut head off, welded 9 5/8" collar, attached BOP, circulated mud out of hole to 3470', circulated clean w/500 bbl., came out of hole w/tubing. Set Halliburton permanent bridge plug @ 3470'. Ran in hole w/RTTS & RBP, acidized perfs 3324-3416' w/1000 gal. 15% NE, swabbed-10-15% oil, fraced w/1000 bbl. Acidized perfs 3146-3245' w/1500 gal. 15% NE, swabbed-4% oil, fraced w/1000 bbl. Acidized perfs 3016-3034' w/1000 gal. 15% NE. Acidized perfs 2734-2782' w/1000 gal. 15% NE. Acidized perfs 2652-2683' w/1000 gal. 15% NE. Fraced perfs 2593-3245' w/3000 bbl. gelled water. Acidized perfs 2376-2498' w/1000 gal. 15% NE, swabbed, no show, fraced w/1000 bbl. gelled water, came out of hole. Put on pump 1/17/83. Well making approximately 25 bbl. oil/day.

Subsurface Safety Valve: Manu. and Type

Set @

Ft

18. I hereby certify that the foregoing is true and correct

SIGNED *[Signature]*

TITLE *Production Clerk*

DATE *2/2/83*

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL IF ANY

TITLE

DATE