

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or complete a well in a different reservoir. Use Form 9-331-C for such proposal.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Tenneco Oil Company

3. ADDRESS OF OPERATOR

6800 Park Ten Blvd., San Antonio, TX. 78213

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 660' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☒

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

SUBSEQUENT REPORT OF:

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

CIBP set at 1880' capped w/35' of cement perforated 1706-1720 w/1JSPF.  
Acidize w/1000 gal 15% NEHCL. Frac w/20,000 gals gelled 2% KCL water and 16,000# sand in 2 equal stages.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Mary Hall*

TITLE Production Analyst

DATE 4-9-80

(This space for Federal or State office use)

APPROVED BY

DATE

CONDITIONS OF APPROVAL, IF ANY:

6. <sup>18</sup>-80 ~~at~~ per Herman ~~for~~  
to P<sub>4</sub>A CIBP @ 1600 w/ 35' cement  
#4h @ 760 + 19.755x lean 20 SX in cag.  
#4h @ 300 + 19.755x " " " "  
spat 255x @ 247  
" " @ surface.

8 7/8" - 247 - 1050  
5 1/2" - 1920 - 150