



NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Kincaid & Watson

(Company or Operator)

Hamble State

(Lease)

Well No. 4, in SE 1/4 of SW 1/4, of Sec 19, T. 17 S, R. 29 E, NMPM.

(Aid) 26.000

Pool,

Eddy

County.

Well is 990 feet from South line and 1250 feet from West line

of Section 19-17-29 If State Land the Oil and Gas Lease No. is E 742

Drilling Commenced 10-30-56, 19 Drilling was Completed 11-7-56, 19

Name of Drilling Contractor O. B. Lewis

Address Roswell, New Mexico

Elevation above sea level at Top of Tubing Head The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 870 to 877 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 265 to 275 feet

No. 2, from to feet

No. 3, from to feet

No. 4, from to feet

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8"	24	NEW	352' 10"	Regular	None	None	Surface
5 1/2"	14	NEW	865	Float	None	None	Oil string

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	8 5/8"	352' 10"	None			
8"	5 1/2"	865	100	Denton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Natural production was approximately 1 BOPD. We sandfree treated with 20,000 gallons of Petrojel service and 38,000 lbs of sand (865-900).

Result of Production Stimulation After treatment the well will make approximately 60 BOPD.

Depth Cleaned Out 900

# WORD OF DRILL-STEM AND SPECIAL TE

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

## TOOLS USED

Rotary tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.  
 Cable tools were used from 0 feet to 955 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.

## PRODUCTION

Put to Producing 11-15-56, 19\_\_\_\_

OIL WELL: The production during the first 24 hours was 60 barrels of liquid of which 100 % was  
 was oil; \_\_\_\_\_ % was emulsion; \_\_\_\_\_ % water; and \_\_\_\_\_ % was sediment. A.P.I.  
 Gravity \_\_\_\_\_

GAS WELL: The production during the first 24 hours was \_\_\_\_\_ M.C.F. plus \_\_\_\_\_ barrels of  
 liquid Hydrocarbon. Shut in Pressure \_\_\_\_\_ lbs.

Length of Time Shut in \_\_\_\_\_

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

### Southeastern New Mexico

T. Anhy. \_\_\_\_\_  
 T. Salt 430  
 B. Salt 580  
 T. Yates \_\_\_\_\_  
 T. 7 Rivers 370  
 T. Queen \_\_\_\_\_  
 T. Grayburg \_\_\_\_\_  
 T. San Andres \_\_\_\_\_  
 T. Glorieta \_\_\_\_\_  
 T. Drinkard \_\_\_\_\_  
 T. Tubbs \_\_\_\_\_  
 T. Abo \_\_\_\_\_  
 T. Penn \_\_\_\_\_  
 T. Miss \_\_\_\_\_

T. Devonian \_\_\_\_\_  
 T. Silurian \_\_\_\_\_  
 T. Montoya \_\_\_\_\_  
 T. Simpson \_\_\_\_\_  
 T. McKee \_\_\_\_\_  
 T. Ellenburger \_\_\_\_\_  
 T. Gr. Wash \_\_\_\_\_  
 T. Granite \_\_\_\_\_  
 T. \_\_\_\_\_  
 T. \_\_\_\_\_  
 T. \_\_\_\_\_  
 T. \_\_\_\_\_  
 T. \_\_\_\_\_

### Northwestern New Mexico

T. Ojo Alamo \_\_\_\_\_  
 T. Kirtland-Fruitland \_\_\_\_\_  
 T. Farmington \_\_\_\_\_  
 T. Picture Cliffs \_\_\_\_\_  
 T. Menefee \_\_\_\_\_  
 T. Point Lookout \_\_\_\_\_  
 T. Mancos \_\_\_\_\_  
 T. Dakota \_\_\_\_\_  
 T. Morrison \_\_\_\_\_  
 T. Penn \_\_\_\_\_  
 T. \_\_\_\_\_  
 T. \_\_\_\_\_  
 T. \_\_\_\_\_

## FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	125	125	Sand & gravel				
125	150	25	Sand & red bed				
150	200	140	Sand & gravel				
200	305	15	Clay				
305	430	125	Red bed				
430	440	10	Salt				
440	450	10	Anhydrite				
450	580	130	Salt				
580	750	170	Anhydrite				
750	816	66	Red bed				
816	855	39	Red rock				
855	870	15	Anhydrite				
870	830	10	Sand & anhydrite				
880	890	10	Anhydrite				
890	898	8	Lime				
898	900	2	Anhydrite & red bed				
900	926	26	Anhydrite & lime				
926	935	9	Anhydrite				
935	940	5	Red rock				
940	955	15	Anhydrite				
955	TD						

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator Kinetic & Watson

Address Box 556, Artesia, N. M.

Name G. Rex Holmes

Position or Title Agent

(Date)