

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

March 21, 1957

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the..... State 8-20
Continental Oil Company Well No. 1 in C
 (Company or Operator) (Unit)
NE 1/4 NW 1/4 of Sec. 20, T. 17S, R. 20E, NMPM, Grayburg-Jackson Pool
 (40-acre Subdivision)
Eddy County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

The subject well was drilled to a total depth of 2400'. 7 5/8" OD casing was set at 706' with 400 sacks cement. A 1 1/2" casing was set at 2397' with 200 sacks cement. A 1 1/2" casing was perforated 2344-2387' and the perforated interval was treated with 500 gallons acid followed with 25,000 gallons foam acid using 30% acid and .1% Alkathene per gallon. No oil or gas was encountered in commercial quantities.

Restoration is requested to plug and abandon the well as follows: Set a 100' (30 sacks) cement plug across perforations 2344-2387'. Set approximately 700' of a 1 1/2" OD casing. Set a 100' (30 sacks) cement plug across top of a 1 1/2" casing and bottom of surface pipe (304'). Set a 50' (12 sacks) plug from surface to 30'. Treat a 4" x 4" section at surface. Restore location to original level.

A subsequent report will be filed upon completion of the above work.

MAR 25 1957

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy M. L. Armstrong
OIL AND GAS DEPARTMENT
Title 7Continental Oil Company
Company or OperatorBy James E. Burns
Position District Superintendent

Send Communications regarding well to:

Name Continental Oil Company
Address Box 400, Hobbs, New Mexico

