

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MAR 19 1957

WELL RECORD

Oil Cons. Comm.
ARTESIA OFFICE

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

Kincaid & Watson
(Company or Operator)

Humble State
(Lease)

Well No. 5, in NW 1/4 of NW 1/4, of Sec. 20, T. 17 S, R. 29 E, NMPM.

Grayburg-Jackson

Pool,

Eddy

County.

Well is 660 feet from West line and 660 feet from North line

of Section 20-17-29. If State Land the Oil and Gas Lease No. is E 742

Drilling Commenced 2-2-57, 19. Drilling was Completed 3-7-57, 19.

Name of Drilling Contractor Kincaid & Watson Drilling Co.

Address Box 530, Artesia, New Mexico

Elevation above sea level at Top of Tubing Head. The information given is to be kept confidential until 19.

OIL SANDS OR ZONES

No. 1, from 1922 to 1936 No. 4, from to

No. 2, from 2430 to 2438 No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 250 to 255 feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8"	24	Used	412	Reg	212.41	None	Surface

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	8 5/8"	412	50	Denton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Plugged & abandoned

Result of Production Stimulation

Depth Cleaned Out

RECORD OF DRILL-STEM AND SPECIAL TESTS.

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from.....feet to.....feet, and from.....feet to.....feet.
Cable tools were used from 0 feet to 2455 feet, and from.....feet to.....feet.

PRODUCTION

Put to Producing Plugged 2-13-57, 19.....

OIL WELL: The production during the first 24 hours was.....barrels of liquid of which.....% was
was oil;% was emulsion;% water; and.....% was sediment A.P.I.
Gravity.....

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of
liquid Hydrocarbon. Shut in Pressure.....lb.

Length of Time Shut in.....

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico				Northwestern New Mexico			
T. Anhy.				T. Devonian			T. Ojo Alamo
T. Salt				T. Silurian			T. Kirtland-Fruitland
B. Salt				T. Montoya			T. Farmington
T. Yates				T. Simpson			T. Pictured Cliffs
T. 7 Rivers				T. McKee			T. Menefee
T. Queen				T. Ellenburger			T. Point Lookout
T. Grayburg				T. Gr. Wash			T. Manos
T. San Andres				T. Granite			T. Dakota
T. Glorieta				T.			T. Morrison
T. Drinkard				T.			T. Penn
T. Tubbs				T.			T.
T. Abo				T.			T.
T. Penn.				T.			T.
T. Miss.				T.			T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	55	55	Caliche	1690	1795	105	Anhydrite
55	160	105	Red rock	1795	1815	20	Lime
160	210	50	Red sandy shale	1815	1830	15	Anhydrite & red rock
210	235	25	Red rock	1830	1905	75	Anhydrite
235	250	15	Anhydrite	1905	1922	17	Anhydrite & red rock
250	255	5	Sand	1922	1935	13	Sandy gray lime
255	275	20	Anhydrite	1935	1940	5	Anhydrite & red rock
275	290	15	Red mud	1940	1970	30	Anhydrite
290	412	122	Red bed	1970	2030	60	Anhydrite & red rock
412	665	253	Salt	2030	2060	30	Anhydrite
665	835	170	Anhydrite	2060	2190	130	Lime
835	880	45	Red rock & anhydrite	2190	2195	5	Sandy lime
880	892	12	Sandy shale & anhy.	2195	2265	70	Lime
892	925	33	Anhydrite & red rock	2265	2285	20	Sandy lime
925	1410	485	Anhydrite	2285	2335	50	Lime
1410	1490	80	Red rock & anhydrite	2335	2345	10	Sandy lime
1490	1670	180	Anhydrite	2345	2360	15	Lime
1670	1690	20	Red sand	2360	2380	20	White lime
				2380	2440	60	Lime
				2440	2445	5	Sandy lime
				2445	2455	12	Lime
				2455	TD		

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator Kincaid & Watson

Address P.O. Box 536, Artesia, N. M.

Name G. Rex Holmes

Position or Title Agent

3-15-57
(Date)