


N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Leonard and Levers, Inc. Roswell, New Mexico
Company or Operator Address
State Well No. 7 in SW SE of Sec. 20, T. 17
Lease
R. 29 N. M. P. M. Leonard Field, Eddy County.
Well is 660 feet north of the North line and 1980 feet west of the East line of section 20
If State land the oil and gas lease is No. B-515 Assignment No. Original
If patented land the owner is Address
If Government land the permittee is Address
The Lessee is Address
Drilling commenced April 29 19 32 Drilling was completed July 20 19 32
Name of drilling contractor Emery Carper Address Artesia, New Mexico
Elevation above sea level at top of casing 3608 feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 943 to 945' Gas Sand, from to
No. 2, from 2167 to 2173 # No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8"	28#			337'					
6 1/2"	26#			2087'					

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	8"	337'	15 sacks			
	6 1/2"	2087'	Mudded			

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from All Cable Tools feet to feet, and from feet to feet

PRODUCTION

Put to producing 19
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Bg
600,000 cu. ft. Upper Sand, 175,000 cu. ft. lower sand
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in. 150# Upper Sand, 560# Lower sand

EMPLOYEES

Emery Carper Driller
Stanley Carper Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 27th day of July 19 32
Place Date
Name Harry Leonard

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	4		Sand
4	255		Gyp and red beds
255	285		Streaks of lime
285	435		Gyp streaks, anhy, red beds, gyp salt
435	620		Salt, gyp, anhy.
620	650		Anhy
650	800		Salt, anhy, red beds, gray shale.
800	943		Anhy, Red beds, red shale.
943	945		Brown sand, gas 600,000'
945	965		Anhy, red sand, brown lime
965	970		Dark grey shale
970	975		Brown lime
975	1115		Anhy, shale, brown lime, brown shale.
1115	1120		Light show of oil
1120	1125		Anhy
1125	1130		Sand, shale, anhy, Oil show
1130	1140		Sand and shale
1140	1260		Anhy, shale, lime, brown shale
1260	1280		Lime, anhy and br. shale
1280	1660		Anhy
1660	1680		Red sand
1680	1698		Anhy
1698	1725		Lime and anhy
1725	1800		Anhy and shale
1800	1820		Lime and anhy
1820	2040		Anhy, lime, shale, sand, red sand.
2040	2122		Lime
2122	2131		Sand
2131	2167		Lime
2167	2173		soft gray sandy lime, 175,000 cu. ft. gas.
2173	2226		Lime, gray sand,
2226	2234		Sand
2234	2248		Gray sand, and lime
2248	2255		Gray lime, hard
2255	2261		Green shale and red sandy shale
2261	2269		Slate
2269			Total depth