

AFTER

PERFORATE COMPANY MACK ENERGY CORPORATIO
 5½ CASING AT LEASE & WELL NO. G.J. WEST COOP UNIT
 FORMATION #34
 60' CIRCULATE COUNTY & STATE EDDY NM
 CEMENT TO SURFACE



RAYMOND MALDONADO
 SUPERVISOR, P & A OPERATIONS
 BUS. (505)393-9171
 FAX (505)393-3848
 MOBILE (505)390-0540

13 3/8 253' CMT W/125 SXS (CIRC.)

TOP OF SALT 262

PERFORATE 5½ CASING AT TOP OF SALT 312' SQUEEZE W/50 SXS CEMENT

BASE OF SALT 660'

PERFORATE 5½ CASING AT 710' SQUEEZE W/35 SXS CEMENT

PERFORATIONS 2246' - 2256'

5½ 2778' CMT. W/150 SXS (T.O.C. 2009')

P.B.T.D. 2750

T.D. 4028'

CONVERSION FACTORS

MULTIPLY	By	TO OBTAIN
Barrels	5.6146	Cubic Feet
Cubic Feet	7.4806	Gallons
Gallons	0.1337	Cubic Feet
Pounds/gal.	7.4806	Pounds/Cu. Ft.

PIPE VOLUMES

0.00545 x I.D.² in inches = Cu. Ft./Ft.
0.0407 x I.D.² in inches = Gals./Ft.
0.00097 x I.D.² in inches = Bbls./Ft.

HYDROSTATIC PRESSURE

FOR WATER:
0.434 x Depth in Feet = PSI.
FOR OTHER FLUIDS:
0.434 x Depth x Sp. Gr. = PSI.