FOLD | MARK

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
10 3/4"	209'	No			
8 5/8"	905	150	Halliburton		
7" C.	2572	100	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material None Length ______ Depth set ______

Adapters—Material None Size ______

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
4"x8'	Bakalite	SNG	330 LBS.	5-11-37	2703'	2757
(ACID)		[illegible]	4000 Gal	[illegible]-37	2703'	2757

TOOLS USED

Rotary tools were used from No feet to ______ feet, and from ______ feet to ______ feet

Cable tools were used from 0 feet to 2757 feet, and from ______ feet to ______ feet

DATES

April 1, 1937, 19___ Put to producing May 16, 19 37.

The production for the first 24 hours was 100 barrels of fluid of which 100 % was oil; 0 % emulsion; 0 % water; and 0 % sediment. Gravity, °Bé. ______

If gas well, cu. ft. per 24 hours ______ Gallons gasoline per 1,000 cu. ft. of gas ______

Rock pressure, lbs. per sq. in. ______

EMPLOYEES

L. E. Pennell, Driller W. L. Barnes, Driller

Pat Gormley, Driller ______, Driller

FORMATION RECORD

FROM	TO	TOTAL FEET	FORMATION
0	30	30	Surface Sand & Red Rock
30	65	35	Gyp
65	70	5	Sand
70	100	30	Gyp
100	130	30	Broken Sand
130	155	25	Red Mud
155	165	10	Blue Shale
165	195	30	Red Rock
[illegible]	[illegible]	10	Gyp
[illegible]	245	40	Red Bed
245	255	10	Gyp
255	270	15	Red Bed
270	310	40	Anhydrite
310	[illegible]	375	Salt
[illegible]	[illegible]	25	Anhydrite
710	[illegible]	40	Broken Anhydrite
[illegible]	[illegible]	95	Anhydrite
845	875	30	Broken Anhydrite
875	[illegible]	5	Shale
[illegible]	[illegible]	25	Red Rock
[illegible]	[illegible]	30	Broken Salt
[illegible]	[illegible]	30	Broken Anhydrite
[illegible]	[illegible]	75	Anhydrite
[illegible]	[illegible]	5	Blue Shale
1040	1090	40	Anhydrite
1090	1095	5	Break

(OVER)

6—0715