

General American Oil Co. of Texas

Page 2

Report of Acid & Sandoil, Burch C-4.

June 12, 1956

RECORD OF FRACTURING (Cont'd):

rec. 1068 bbls. Used 4 Fracmasters & 1 blender 35 by Western Co.

RESULTS OF FRACTURING:

- 5-29 Ran 2735.84' (88 jts.) 2" reg. & 469.32' (15 jts.) 2" EUE tubing
w/15.12' of 2" reg. anchor. Total string 3219.28'.
Flowed 711 BO in 23 hrs. thru 3/4" tubing choke.
5-30 Flowed 465 BO in 24 hrs. thru 3/4" tubing choke. NET 106 BO.

SUBSEQUENT TESTS:

- 6-10 Flowed 92 BO in 4 - 1 hr. flows.

1944 to 1945 in the United States

the 1990s, the number of people in the world who are under 15 years of age is expected to increase from 1.1 billion to 1.5 billion. The number of people aged 65 and over is expected to increase from 250 million to 450 million. The number of people aged 15 and over is expected to increase from 3.5 billion to 4.5 billion. The number of people aged 15 and over is expected to increase from 3.5 billion to 4.5 billion. The number of people aged 15 and over is expected to increase from 3.5 billion to 4.5 billion.

[illegible]

ALL INFORMATION CONTAINED HEREIN IS UNCLASSIFIED

Abstract

...the
... ..
... ..
... ..

... ..

THE UNIVERSITY OF CHICAGO

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Las CrucesLease No. 028791 (a)Unit Arch. C

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Loos Mills, New Mexico, 1956Well No. 4 is located 1980 ft. from N line and 1940 ft. from E line of sec. 23SW 1/4 Sec. 23
(1/4 Sec. and Sec. No.)17-3
(Twp.)27-3
(Range)T. 17 N., R. 27 E.
(Meridian)Grayburg-Loos
(Field)2447
(County or Subdivision)New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On May 22, 1956 we ran 3005' of 3 1/2" 110 lb. 60 lb. 4-55, SMC, and 30' less Pittsburgh casing to 3267' and cemented with 55 sacks Alaska cement.

After allowing to stand cemented 1 hour we ran temperature survey. Survey showed top of cement at 2760'.

After allowing to stand cemented for 72 hours, we drilled plug, bailed it out and re-ran bailer.

As shut-off to proved complete drilling was resumed. Cementing was done by Benton Oil Well Cementing Co.

Temperature survey was run by West & Seng Co.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company General American Oil Company of TexasAddress P. O. Box 416Loos Mills, N. M.By R. J. HeariTitle A. J. Heari
Field Superintendent