

U. S. LAND OFFICE
LOS ANGELES
SERIAL NUMBER 028784-9387
LEASE OR PERMIT TO PROSPECT

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

LOCALITY CORRECTLY
JUL 6 1953
Don Bonnes
ALL INFORMATION CONTAINED
HEREIN IS UNCLASSIFIED
DATE 11/18/01 BY 60322
Company
Address
Box 2197, North

Well No. 1 Sec. 24 T. 17-S. R. 29-E Meridian ~~W~~ County ~~W~~ Elevation 3587' Location 660 ft N. { of 3 Line and 560 ft E. } of 4 Line of Sec. 24 (Derick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Date April 29, 1953 Time 11:00 AM. 2000

The summary on this page is for the condition of the well at above date.

Commenced drilling April 25, 1952 Finished drilling February 1, 1953

OIL OR GAS SANDS OR ZONES

No. 1, from	to	No. 4, from	to
No. 2, from	to	No. 5, from	to
No. 3, from	to	No. 6, from	to

CASING RECORD

Size each	Weight per foot	Threads per inch	Gauge	Amount	Kind of shoe	Cut and pulled from	From—	To—	Purpose
3-3/8"	61#	8 HI	HS	300#	8 HI				
3-5/8"	36#	8 HI	HS	343#	8 HI				
7"	2629#	8 HI	HS	1113#	8 HI				

RECORDING AND CEMENTING RECORD

Site (east)	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
3-3/4"	310'	650	ROVER		Amount of mud used 300
9-5/8"	352'	250	ROVER		Amount of mud used 300
7"	1167'	515	ROVER		Amount of mud used 300

PLUGS AND ADAPTERS

Heaving plug--Material	Adapters--Material
Size	Length

SHOOTING RECORD

[illegible]

TOOLS USED

Tool	Feet to	Feet and from
Rotary tools were used from	11.5'	feet to 13.31' feet, and from
Cable tools were used from	0'	feet to 1.13' feet, and from

DATES

The production for the first 24 hours was ----- barrels of fluid of which ----- % was oil; -----

Well	Gas well, cu. ft. per 24 hours	Oil well, cu. ft. per 24 hours	Water, gal. per 24 hours	Gas, cu. ft. per 1,000 cu. ft. of gas
1				
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				
15				
16				
17				
18				
19				
20				
21				
22				
23				
24				
25				
26				
27				
28				
29				
30				
31				
32				
33				
34				
35				
36				
37				
38				
39				
40				
41				
42				
43				
44				
45				
46				
47				
48				
49				
50				
51				
52				
53				
54				
55				
56				
57				
58				
59				
60				
61				
62				
63				
64				
65				
66				
67				
68				
69				
70				
71				
72				
73				
74				
75				
76				
77				
78				
79				
80				
81				
82				
83				
84				
85				
86				
87				
88				
89				
90				
91				
92				
93				
94				
95				
96				
97				
98				
99				
100				

EMPLOYEES

Driller, _____

FORMATION RECORD

FROM -	TO -	TOTAL FEET	FORMATION

15-00000-0-1125

Distance from center floor to top of hole	Material	Weight
0	Red Rock	1.75
15	Red Rock	13.25
25	Red Rock	19
30	Red Rock	5
50	Red Rock	20
70	Red Rock	20
95	Red Rock	25
120	Red Rock	25
140	Red Rock	20
180	Red Rock	40
255	Red Rock	75
265	Red Rock	10
295	Red Rock	30
325	Red Rock	30
360	Red Rock	35
605	Red Rock	24.5
630	Red Rock	25
790	Red Rock	150
1013	Red Rock	203
1032	Red Rock	19
1073	Red Rock	41
1099	Red Rock	26
1125	Red Rock	26

FORMATION RECORD—Continued

FROM—	TO—	TOTAL FEET	FORMATION
FORMATION FROM 1125-13.341' ARE MEASURED FROM KELLY DRIVE BEARING 16.30' ABOVE GROUND			
	1115	-10	(All correct depth from Kelly Drive bearing before Rotary started drilling)
	1266	151	Anhydrite
	1412	146	Anhydrite and lime
	1595	183	Anhydrite and Potash
	1776	181	Anhydrite, Potash and lime
	1816	40	Anhydrite and Potash
	1915	99	Lime, anhydrite and Potash
	1934	19	Anhydrite and lime
	2660	726	Lime and Anhydrite - Reached 1,000' 4:30 AM 6-7-52
	2693	33	Lime, anhydrite and Gyp
	3364	671	Lime and Anhydrite - Reached 3,000' 9:PM 6-10-52
	3414	50	Lime, anhydrite and Potash - Reduced to 8-3/4" Hole at 3453'
	3523	109	Lime and Anhydrite
	3587	64	Sandy Lime
	3674	107	Lime and Anhydrite
	3691	17	Hard Sandy lime and anhydrite
	3742	51	Lime and anhydrite
	3751	9	Lime, Sand and anhydrite
	4143	392	Lime and Anhydrite - Reached 4,000' 2:AM 6-30-52
	4198	55	Lime and Sand
	4308	110	Lime and anhydrite
	4344	36	Lime
	4432	88	Lime and Anhydrite
	4505	73	Lime
	4574	69	Lime and Anhydrite
	4666	92	Lime
	4684	18	Lime and Hard Sand
	4708	24	Lime and Dolomite
	5060	352	Lime - Reached 5,000' 9:PM 7-9-52
	5114	54	Lime and Chert
	5152	38	Lime
	5350	198	Lime and Chert
	5496	146	Lime
	5513	17	Lime and Chert
	6218	705	Lime - Reached 6,000' 6:PM 7-23-52
	6242	24	Lime and Chert - Reached 7,000' 11:PM 8-7-52
	8170	1928	Lime - Reached 8,000' 7:AM 8-30-52
	8191	21	Lime and Shale
	8381	190	Lime
	8420	39	Lime and Shale
	8480	60	Lime
	8490	10	Lime and Shale
	8531	41	Lime
	8569	38	Lime and Shale
	8595	26	Lime
	8753	158	Lime and Shale
	8850	97	Lime
	8893	43	Lime and Shale
	9000	107	Lime - Reached 9,000' 8:AM 9-16-52
	9010	10	Lime and Shale
	9011	1	Lime
	9182	171	Lime and Shale
	9884	702	Lime
	9930	48	Lime and Shale
	10795	865	Lime - Reached 10,000' 7:PM 10-1-52
	10807	12	Lime and Chert
	10840	33	Lime
	10853	13	Lime and Shale

HISTORY OF OIL OR GAS WELL

16-43024-1

U. S. GOVERNMENT PRINTING OFFICE

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of redrilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked" or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing.