

N. M. D. C. C. COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-028784-a

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Keely A

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 24, T-17S, R-29E.

12. COUNTY OR PARISH

Eddy

13. STATE
N. Mex.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

General American Oil Company of Texas

3. ADDRESS OF OPERATOR

P. O. Box 416, Loco Hills, New Mexico 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State regulations. See also space 17 below.)
At surface 1980' FSL and 1980' FWL, Sec. 24, T-17S, R-29E.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3599' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-8 We perforated as follows: 2342'-2350', 2452'-2456', 2461'-2463', 2484'-2489', 2686'-2693', 2818'-2821', 2872'-2875', 2936'-2943', 2956'-2960', 3068'-3071', 3104'-3110', 3155'-3160', 3186'-3191', 3224'-3228', 3346'-3349', 3370'-3374'.

3-9 Fraced from 3346' to 3374' with 30,000# sand and 30,000 gallons water.
Fraced from 3155' to 3228' with 10,000# sand and 10,000 gallons water, Sanded out.
Fraced from 3068' to 3110' with 30,000# sand and 30,000 gallons water,
Acidized from 2936' to 2960' with 3500 gallons.
Attempted to acidize from 2818' to 2875' and communicated. Shut down.

3-10 Fraced from 2452' to 2489' with 30,000# sand and 30,000 gallons water.
Fraced from 2342' to 2350' with 30,000# sand and 30,000 gallons water.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. E. Walter

TITLE

District Superintendent

DATE

March 15, 1972

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

RECEIVED

MAR 16 1972

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

APPROVED
MAR 16 1972

R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

847 - 485