

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)

Budget: Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

LC-028784-4

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

C/SF

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Keely A Federal

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

Gb-J-SR-Q-Gb-SA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

24,17-S, 29-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

OIL WELL ☐ GAS WELL ☐ OTHER Wtr. inj. per NMOC order #R.7900

2. NAME OF OPERATOR

Phillips Petroleum Company

3. ADDRESS OF OPERATOR

4001 Penbrook St., Odessa, Texas 79762

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

Unit K, 1980' ENL & 1980' FWL

14. PERMIT NO.

API No. 30-015-03071

15. ELEVATIONS (Show whether OF, BT, OR, etc.)

3578' GR

JAN 26 1987

ARTESIA, OFFICE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Convert to wtr. inj.

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

10-9-86: RU WSU. Unseated pmp. Pulled sucker rods & 2" X 1 1/2" X 10' pmp. Installed BOP. Pulled 2-3/8" production tbg. WIH w/6 1/4" bit & 7" csg scraper to top of liner @ 2703'. Tst'd 2-3/8" tbg to 5000# above slips while going in hole. POH. WIH w/7" pkr on tbg to 2258'. Press'd annulus to 500# for 15 min to verify csg integrity, tst'd ok. Released pkr, COOH.

10-10 thru

10-12-86: Cleaned out well to 3563'. Loaded hole w/98 bbls 2% KCL wtr. Spotted 26 bbls 10% acetic acid from 3350'-2300'. Ran gamma ray/collar locator log from PBTD-2300'. Perf'd w/3-3/8" OD csg guns below 2700' & 4" OD csg guns above 2700', 2SPF 2316'-2318'; 2321'-2323'; 2389'-2391'; 2418'-2422'; 2515'-2517'; 2566'-2568'; 2573'-2575'; 2595'-2597'; 2647- 2649'; 2676-2678'; 2730'-2732; 3312'-3314'. Well SI 48 hrs.

10-13-86: Set 7" pkr @ 2280'. Acidized San Andres interval w/8000 gals of 15% NEFE HCL. Annulus loaded w/2% KCL wtr. Pressure tested lines to 5000#, ok. Swbd 10 BLW. Set pkr @ 2257'. Trt'd Graybrug perms w/3500 gals 7 1/2% NEFE HCL.

10-14-86: Released pkr. WIH w/7" Brown Oil Tool plastic coated pkr on 2-3/8" plastic coated tbg to 2269'. Displaced hole w/2% KCL wtr containing 1% by volume of Techni-hib 370. Set pkr @ 2269', tst'd csg to 500 psi for 15 min, ok.

Dropped from report until water injection commences.

18. I hereby certify that the foregoing is true and correct

SIGNED W. J. Mueller

TITLE Engr. Supv., Resv.

DATE 1-15-87

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD
DATE

JAN 16 1987

*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO

