

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other ☐
b. TYPE OF COMPLETION: NEW WELL ☐ WORK OVER ☐ DEEP-EN ☒ PLUG BACK ☐ DIFF. RESVR. ☐ Other ☐

2. NAME OF OPERATOR
General American Oil Company of Texas3. ADDRESS OF OPERATOR
P. O. Box 416 Loco Hills, New Mexico 88250

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface

25' FNL and 1295' FNL**Sec. 25- T17S - R29E**

At top prod. interval reported below

At total depth

14. PERMIT NO. DATE ISSUED

APR 9 1973

15. DATE SPUDDED **2-12-73** 16. DATE T.D. REACHED **2-22-73** 17. DATE COMPL. (Ready to prod.) **3-14-73** 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* **3611 DF** 19. ELEV. CASINGHEAD **3610**

20. TOTAL DEPTH, MD & TVD **3602** 21. PLUG, BACK T.D., MD & TVD **3596** 22. IF MULTIPLE COMPL., HOW MANY* **3** 23. INTERVALS DRILLED BY **→** ROTARY TOOLS CABLE TOOLS **3602'**

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

2508' - 3567' Grayburg and San Andres

25. WAS DIRECTIONAL SURVEY MADE

NO

26. TYPE ELECTRIC AND OTHER LOGS RUN

BWM, GR and Caliper

27. WAS WELL CORED

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	28	455'	11'	60 sacks	NONE
7"	20	2692'	8 1/4"	100 sacks	NONE

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
4 1/2"	2637'	3602'	120		2 3/8" BUE	3550"	
9.50							

31. PERFORATION RECORD (Interval, size and number)

**2508'-2511'; 2565'-2568'; 2572'-2574';
2596'-2599'; 3073'-3075'; 3103'-3105';
3120'-3122'; 3314'-3316'; 3331'-3334';
3338'-3340'; 3517'-3522'; 3564'-3567'.**

32. ACID, SHOT, FRACTURE, OR OTHER SPECIAL TREATMENT

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
	APR 5 1973
	See Reverse Side

33.* PRODUCTION

DATE FIRST PRODUCTION **March 21, 1973** PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) **Pumping** WELL STATUS (Producing or shut-in) **Producing**

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
3-29-73	24		→	25	27	80	
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
		→	25	27	80		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Sold to Phillips

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

Logs

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

W. E. Hattis

TITLE

District Superintendent

DATE

April 5, 1973

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES			38. GEOLOGIC MARKERS				
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TOP	TRUE VERT. DEPTH
Graybury Dolo.	2508'	2511'	Dolomite show oil				
Matax Sand	2560'	2600'	Sand stringers oil stain				
San Andres	2950'	3570'	Dolomite stain and porosity in spots.				
Fraced from	3517'	3567'	With 24,000# sand and 24,000 gallon water.				
Fraced from	3314'	3340'	With 36,000# sand and 36,000 gallon water.				
Acidized from	3073'	3122'	With 3,500 gallon.				
Fraced from	2508'	2599'	With 30,000# sand and 30,000 gallon water.				