

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
SUBMIT IN TRIPLICATE
(Other instructions on reverse side)
88210

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water injection		RECEIVED BY JAN 26 1987 O.C.D. ARTESIA OFFICE JAN 16 1987		5. LEASE DESIGNATION AND SERIAL NO. LC-028784-c	
2. NAME OF OPERATOR Phillips Petroleum Company				6. IF INDIAN, ALLOTTEE OR TRIBE NAME C/SF	
3. ADDRESS OF OPERATOR 4001 Penbrook St., Odessa, Texas 79762				7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements in effect at surface. See also space 17 below.) Unit E, 1980'FNL & 660'FWL				8. FARM OR LEASE NAME Keely C Federal	
				9. WELL NO. 10	
				10. FIELD AND POOL, OR WILDCAT Gb-J-SR-Q-Gb-SA	
				11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 25,17-S, 29-E	
14. PERMIT NO. API NO.30-015-03090		15. ELEVATIONS (Show whether DF, ST, GR, etc.) 3596'DF		12. COUNTY OR PARISH Eddy	
				13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Water injection

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

12-3-86: 3165'PTD. RU WSU. COOH w/rods & sucker rod pmp. Installed BOP.

12-4 thru

12-7-86: Drld out cmt & ClBP @ 3000'. WIH w/RTTS-type pkr on 2-7/8" work string, set pkr @ 2400'. Well SI 48 hrs.

12-8-86: COOH w/tbg & pkr. WIH w/RTTS-type RBP & pkr, set pkr @ 2,900', RBP @ 2,940', tst'd RBP to 1000 psi, tst'd OK. Spt'd 16 bbls 10% Acetic acid from 2900'-2500'. Ran GR/collar locator log from 2940-2000'. Perf'd 7" csg using 4" OD csg gun 2SPF @ 2520'-2522'; 2630'-2632'; 2674'-2676'; 2704'-2706'; 2722'-2726'; 2734'-2736'; 2814'-2816'; 2852'-2854'; 2858'-2860'; 2872'-2874'.

12-9-86: Acidize Grayburg perfs w/4200 gals 7½% NEFE HCL.

12-10-86: WIH w/7" Brown Oil Tool plastic coated pkr on 2-3/8" plastic coated tbg to depth of 2391'. Removed BOP.

12-11-86: Displaced tbg-csg annulus w/2% KCL wtr containing packer fluid. Set pkr @ 2391' in 10,000# tension. Pressure test csg to 500# for 15 min, tst'd OK. Installed wellhead injection assembly.

Waiting on commencement of water injection.

ACCEPTED FOR RECORD

JAN 16 1987

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

W. J. Mueller

TITLE Engr. Supv., Resv.

DATE 1-15-87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Post ID-3
2-6-87
chg from prod.