


(SUBMIT IN TRIPLICATE)

Land Office Las CrucesLease No. 008701-CUnit Leely "C"

APPROVED



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	Subsequent Report of Hydrofracture and Acidfract

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Leeco Hills, New Mexico Nov. 22, 1954Well No. 12-C is located 1980 ft. from N line and 1980 ft. from E line of sec. 25SW 1/4 Sec. 25 17-2 22-2 N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)Grayburg 244 New Mexico
(Field) (County or Subdivision) (State or Territory)The elevation of the derrick floor above sea level is 3590 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

RECORD OF PRODUCTION PRIOR TO TREATMENT: Pumped 15 BOPD. Total Prod. 99.148 BO.**RECORD OF RECOMPLETION:****10-18-54** Run Leeco-Hills radioactivity survey from 3270 back to surface. Perforated with 7 1/2 (15/32") bullets from 2620-43 and with 25 (15/32") bullets from 2543-49.**10-19-54** Run straddle packer on 2-1/2" EUE tubing with Gullerson KV H-W. at 2654; 1 jt. rgs. 2; EAV anchor packer & H-1 hydraulic anchor at 2617; tubd. dry. After standing 1 hr., ran comb & rec. 20" of oil from tubing. Treated with 500 gals. HCl. Num. inj. press. 1900 psig; at end of flush 1400 psig. Total inj. time 5 min. Shut in 3 hrs, cold. oil flush & acid water.**10-20-54** After standing 16 hrs, rec. 130" of oil from 2-1/2" EUE. Fractured as follows: 25 bbls. of 47.9 deg. distillate; 3,000 gals. hydrofract

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

(Continued on page #2)

Company GENERAL AMERICAN OIL COMPANY OF TEXASAddress Box 416LECO HILLS, N. M.By R. J. Heard
R. J. HeardTitle Field Supt.