

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
Artesia, NM 88210

SUBMIT IN THIS
DRAWER DD

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-028784-c

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Keely "C"

9. WELL NO.

23

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 25, T-17S, R-29E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

General American Oil Company of Texas

3. ADDRESS OF OPERATOR

P. O. Box 128 Loco Hills, New Mexico 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirement.)

See also space 17 below.)
At surface

660' FSL and 660' FWL

NOV 23 1981

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3579' DF

ARTESIA, OFFICE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10-1-81 Ran Dresser-Atlas Acoustilog with gamma ray curve.

10-19-81 Perforate as follows: 2536'-2540' 2 holes per foot
2546'-2553' 2 holes per foot
2624'-2626' 2 holes per foot
2664'-2673' 2 holes per foot

10-22-81 Treat San Andres open hole section with 3,500 gallons 15% N.E. acid.

10-23-81 Treat perforations 2624'-2626' and 2664'-2673' with 25,000 gallons gelled water containing 25,000# 20/40 mesh bulk sand.

10-24-81 Treat perforations 2536'-2540' and 2546'-2553', with 30,000 gallons gelled water containing 30,000# 20/40 mesh bulk sand.

10-29 thru

11-5-81 Pumping undetermined amount of load water to pit.

11-6-81 Pumped 36 barrels of oil per day and undetermined amount of water.

11-7-81 Pumped 34 barrels of oil per day and undetermined amount of water.

11-8-81 Pumped 40 barrels of oil per day and undetermined amount of water.

18. I hereby certify that the foregoing is true and correct

SIGNED M. S. Lansing

TITLE Engineer

DATE November 10, 1981

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

NOV 20 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side