

UNITED STATES Artesia, NM 88210  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐  
well well other

2. NAME OF OPERATOR

General American Oil Company of Texas ✓

3. ADDRESS OF OPERATOR

P. O. Box 128, Loco Hills, New Mexico 88255

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FSL and 1980' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☒

☒

☐

☐

☐

☐

☐

5. LEASE

LC-028784-c

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

RECEIVED

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Keely C

9. WELL NO.

#25

10. FIELD OR WILDCAT NAME

Grayburg Jackson

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 25, T-17-S, R-29-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3582 DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

DEC 16 1982

OIL & GAS  
MINERALS MGMT. SERVICE  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12/8/82 Perforated Metex from 2780-86' and from 2749-55' (2 shots per foot). Sand fraced with 30,000# 20/40 sand and 30,000 gallons gelled water.

Perforated Grayburg Dolomite 2677-81' (2 shots per foot). Acidized with 3,000 gallons of 15% NE acid.

Perforated Loco Hills from 2622-26' and from 2611-16' (2 shots per foot). Sand fraced with 20,000# 20/40 sand and 20,000 gallons gelled water.

Placed well on test.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Pendall M. Hawkins TITLE Field Supt. DATE December 10, 1982

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY V. CHESTER TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL \_\_\_\_\_

JAN 17 1983

MINERALS MANAGEMENT SERVICE  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side