

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other ☐b. TYPE OF COMPLETION: NEW WELL ☐ WORK OVER ☐ DEEP-EN ☒ PLUG BACK ☐ DIFF. RESVR. ☐ Other ☐2. NAME OF OPERATOR
General American Oil Company of Texas3. ADDRESS OF OPERATOR
P. O. Box 416 Loco Hills, New Mexico 88253

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface

25' FNL and 1295' FNL

Sec. 25- T17S - R29E

At top prod. interval reported below

At total depth

14. PERMIT NO. DATE ISSUED

12. COUNTY OR PARISH
Eddy13. STATE
New Mexico

15. DATE STUDDED 2-12-73 16. DATE T.D. REACHED 2-22-73 17. DATE COMPL. (Ready to prod.) 3-14-73 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 3611 DF 19. ELEV. CASINGHEAD 3610

20. TOTAL DEPTH, MD & TVD 3602 (3141) 21. PLUG BACK T.D., MD & TVD 3596 22. IF MULTIPLE COMPL., HOW MANY* 23. INTERVALS DRILLED BY 24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 2508' - 3567' Grayburg and San Andres 25. WAS DIRECTIONAL SURVEY MADE NO

26. TYPE ELECTRIC AND OTHER LOGS RUN SWM, GR and Caliper 27. WAS WELL CORED

28. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	28	455'	11'	60 sacks	NONE
7"	20	2892'	8 1/4"	100 sacks	NONE

29. LINER RECORD					30. TUBING RECORD		
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
4 1/2"	2837'	3602'	120		2 3/8" BBL	3550"	
9.54							

31. PERFORATION RECORD (Interval, size and number)
2508'-2511', 2565'-2568', 2572'-2574',
2596'-2599', 3073'-3075', 3103'-3105',
3120'-3122', 3314'-3316', 3331'-3334',
3338'-3340', 3517'-3522', 3564'-3567'.

32. ACID, SHOT, FRACTURE, GEL, SQUEEZE, ETC.	
DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
	See Reverse Side

33.* PRODUCTION							
DATE FIRST PRODUCTION March 21, 1973		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Pumping				WELL STATUS (Producing or shut-in) Producing	
DATE OF TEST 3-29-73	HOURS TESTED 24	CHOKE SIZE	PROD'N. FOR TEST PERIOD →	OIL—BBL. 25	GAS—MCF. 27	WATER—BBL. 80	GAS-OIL RATIO
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE →	OIL—BBL. 25	GAS—MCF. 27	WATER—BBL. 80	OIL GRAVITY-API (CORR.)	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)
Sold to Phillips35. LIST OF ATTACHMENTS
Logs

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED W. C. Harte TITLE District Superintendent DATE April 5, 1973

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 88, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers', geologists', sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

On 18 October 2018, the following information was provided by the applicant:

Item 22: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Item 23: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Item 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool. For each additional interval to be separately produced, showing any additional data pertaining to such interval.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TOP TRUE VERT. DEPTH
Grayburg Dolo.	2508'	2511'	Dolomite show oil			
Metex Sand	2560'	2600'	Sand Stringers oil stain			
San Andres	2950'	3570'	Dolomite stain and porosity in spots.			
Fraced from	3517'	3567'	With 24,000# sand and 24,000 gallon water.			
Fraced from	3314'	3340'	With 36,000# sand and 36,000 gallon water.			
Acidized from	3073'	3122'	With 3,500 gallon.			
Fraced from	2508'	2599'	With 30,000# sand and 30,000 gallon water.			