

(SUBMIT IN TRIPLICATE)

Land Office Los Gatos

Lease No. 226734(e) C

Unit Early "C"

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

APPROVED

OCT 26 1954

DISTRICT ENGINEER

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

Subsequent Report of Hydrofracture & Acidfracture

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Los Hills, N. M. October 21, 1954

Well No. 34-C is located 2615 ft. from 1/4 line and 1295 ft. from E line of sec. 25

25 (1/4 Sec. and Sec. No.) 17-N (Twp.) 29-E (Range) N.M.P.M. (Meridian)
Comstock-Jackson (Field) 244 (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 3500 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)
RECORD OF PRODUCTION PRIOR TO TREATMENT: Pumped 12 BOPD.

RECORD OF RECOMPLETION:

- 9-22-54 Run long-wells radioactive survey from 3522 back to surface. Perforated with 7 1/2 - 15/32" bullets from 2625-2700 ft. and 2 1/2 - 15/32" bullets from 2775-2850 ft.
- 9-23-54 Run straddle packer on 2-1/8" EUE tubing with Galbraith XV-30 H-W packer at 2700 and KAV anchor packer and H-1 hydraulic anchor at 2661.
- 9-24-54 After standing 16 hrs, run sand & rec. show of gas. Treated with 500 gals. H2A. Max. inj. press. 1800 psigs at end of flush 1500 psig. Total inj. time 12 min. Total oil flush & acid water.
- 9-25-54 Run sand & rec. 1/2" of oil from 2-1/8" EUE. Fractured with 1500 gals. barosone; 3,000 gals. hydrofracture containing 600 lbs. sand; then 600 lbs. breaker fluid. Flashed with 110 BOP. Max. inj. press. 2700 psigs at end

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

(Continued on page 2)

Company General American Oil Company of Texas

Address Box 416

Los Hills, N. M.

By

R. J. Heard

Title R. J. Heard
Field Supt.