

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐  
well well other

2. NAME OF OPERATOR PHILLIPS OIL COMPANY, AS successor  
to General American Oil Co. of Texas, by merger 3-8-83

3. ADDRESS OF OPERATOR  
Room 401, 4001 Penbrook St., Odessa, TX 79762

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: Unit N, 1295' FS & 1345' FW lines  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input checked="" type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input checked="" type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other) Add perforations			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Current OH 3015'to3265', and perfs 2586-98'. PROPOSE TO ADD perforations 2965-74', treat with gelled brine and acid, frac w/57000# sand in 32000 gals UAG-3/11 w/biocide; add perforations 2523-2815' (selectively), treat w/acid, frac perfs 2523-2815' w/52000 gals refined oil w/68000# sand.  
Clean out frac sand, run production tubing, rods and pump. Restore to production.

BOP Eqpt.: Series 900, 3000# test, double, with one set pipe rams and one set pipe rams, manually operated.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Senior Engineering Specialist DATE 8-3-83  
(This space for Federal or State office use)

APPROVED BY (C. Sgd.) PETER W. CHESTER TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

AUG 16 1983

5. LEASE LC-028784-c
6. IF INDIAN, ALLOTTEE OR TRIBE NAME --
7. UNIT AGREEMENT NAME --
8. FARM OR LEASE NAME Keely-C FED
9. WELL NO. 36
10. FIELD OR WILDCAT NAME Grayburg-Jackson (7R-Q-Gb-SA)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 25, T-17-S, R-29-E
12. COUNTY OR PARISH Eddy
13. STATE New Mexico
14. API NO. --
15. ELEVATIONS (SHOW DF, KDB, AND WD) 3580' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED  
AUG 4 10 29 AM '83  
BUR. OF LAND MGMT.  
ROSSELL DISTRICT