

95F

UN. STATES
DEPARTMENT OF THE INTERIOR COMMISSION C-028784-C
GEOLOGICAL SURVEY
New Mexico Oil Cons. Commission
Drawer DD
Artesia, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR Phillips Oil Company, as successor to General American Oil Co., of Tx by merger 3-8-83

3. ADDRESS OF OPERATOR
Room 401, 4001 Penbrook, Odessa, Texas 797624. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: Unit N, 1295' FSL, 1345' FWL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Add Perforations

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED BY

OCT 14 1983

O. C. D.

ARTESIA, OFFICE

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Continued from report dated 9-20-83

9-19-83: Pmpd 24 hrs, 82 BLO, 14 BW. Trace of oil.

9-20,21-83: Pmpd 48 hrs, 127 BLO, 14 BW.

9-22-83: Pmpd 24 hrs, 46 BLO, 4 BW.

9-23,24

& 25-83: Pmpd 72 hrs, 136 BLO, 84 BW.

9-26-83: Pmpd 9 BO, 35 BLO, 48 BW.

BOP EQUIP: Series 900, 3000# WP, double w/l set pipe rams, 1 set blind rams, manually operated
Subsurface Safety Valve: Manu. and Type _____ Set @ _____

18. I hereby certify that the foregoing is true and correct

SIGNED W.J. Mueller TITLE Senior Engineering Specialist DATE 10-6-83

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

ACCEPTED FOR RECORD

OCT 12 1983

*See Instructions on Reverse Side

ROSWELL, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1981 O - 347-166

9-27-83: Ran wtr sample on well before completion, CL 33,420, sulfate 967, trace of carbonate, biocarbonate 520, sodium 25, 630, calcium 6,500, magnesium 2,950, PH 7, specific gravity 1.027. Pmpd 24 hrs, 43 BW, 43 BW, GOR: 140 from 7" csg perfs 2523' to 2974' & open hole interval 3015' to 3265'. Single completion in Grayburg/san Andres formation. Well returned to production.