

(SUBMIT IN TRIPLICATE)

Land Office Las CrucesLease No. 00070-93(b) Tr. A.Unit Block 8

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

|  |   |
|--|---|
| NOTICE OF INTENTION TO DRILL                   | SUBSEQUENT REPORT OF WATER SHUT-OFF                 |
| NOTICE OF INTENTION TO CHANGE PLANS            | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING          |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF     | SUBSEQUENT REPORT OF ALTERING CASING                |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR          |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE        | SUBSEQUENT REPORT OF ABANDONMENT                    |
| NOTICE OF INTENTION TO PULL OR ALTER CASING    | SUPPLEMENTARY WELL HISTORY                          |
| NOTICE OF INTENTION TO ABANDON WELL            | <u>Subsequent Report of Acid Petroleum</u> <u>x</u> |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Love Hills, New Mexico Oct. 26, 1954Well No. 21-3 is located 2815 ft. from N line and 2815 ft. from E line of sec. 26

21-4 Sec. 26 17-3 23-1 N. 100° E.  
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Grayburg-Jackson 244 New Mexico  
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3571 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

**RECORD OF PRODUCTION FROM TO TREATMENT: Flowed 10 BOP.**

## RECORD OF COMPLETION:

10-7-54 Pulled tubing & bailed.10-8-54 Run 54 lbs. 2-1/2" 200 tubing to 2789' with Stribron 6-2 1/2" packer & 2-1 hydraulic anchor at 2774'. Intd. Gr. Loaded annulus with 90 BOP.10-9-54 After standing 16 hrs. ran ann. & rec. 10 BOP. Fractured with 30 lbs. crude oil; 1,000 gals. acid petroleum containing 1 lb. sand per gal; 1,000 gals. containing 1-1/2 lbs. and 1075 gals. with 2 lbs. At this point well started up. Pulled tubing, started snubbing casing. Load oil to rec. 120 lbs.

## RESULTS OF TREATMENT:

10-10-54 Snubbed 24 lbs. in 3 hrs.10-11-54 Snubbed 24 lbs. in 3 hrs.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

(See 2. on page 2)

Company General American Oil Co. of TexasAddress Box 116Love Hills, N. M.

By

R. J. Board  
R. J. BoardTitle Field Sup.

General American Oil Co. of Texas

Page #2

Subsequent Report of Acid Petrobras, Kooly B-21.

Oct. 26, 1954

**RESULTS OF TREATMENT (Cont'd).**

10-12-54 Swabbed 56 bbls. in 8 hrs. (NET 24 BO).

10-13-54 Swabbed 14 BO. Ran pump installation.

**SUBSEQUENT TESTS:**

10-22-54 Pumped 24 BO.

10-23-54 Pumped 24 BO.

10-24-54 Pumped 17 BO.

10-25-54 Pumped 17 BO.

Page 2

General Assistant 11101 of 10000

1000 00 00

Independent Report of 1000 00 00

(1000 00 00) 1000 00 00  
10-10-01 1000 00 00  
10-10-01 1000 00 00  
10-10-01 1000 00 00

1000 00 00

10-10-01 1000 00 00  
10-10-01 1000 00 00  
10-10-01 1000 00 00  
10-10-01 1000 00 00