· RELE	BAD BY	DEPAR			Chill Actue Bidel	U. L.	SE DESIGNATION	AND SERIAL NO.
	1005	BURE	AU OF LAND M	ANAGEMENT	a. M. 00010		-028784-#	
SEP 11	SUND		TICES AND F			6. tr 1	INDIAN, ALLOTTE	E OR TRIBE NAME
(Be net	up this for		•••=•		ack to a different reservoir.			
ARTESIA,	OFFICE					7. UNI	T AGREEMENT N	A M E
WELL X	GAS WELL	OTHER				•		
NAME OF OP				1		8. FAR	M OR LEASE NA	NR
-	os Petro	leum C	ompany 🖌		SEDA		ely B Fed	
ADDRESS OF		F 1	1 2 21	•	1985	9. WBI	J. NO.	· · · · · · · · · · · · · · · · · · ·
KOOM 40)1, 4001	Penbr	ook St., Ode	ssa, Texas	s 79762	12	LD AND POOL, C	
See also spa At surface	ce 17 below.		· · · · · · · · · · · · · · · · · · ·		, Hick I		_	
(Unit P) 660'FSL & 660'FEL					3. A.	Grayburg Jackson (SR-Q-Gl 11. SBC, T., E., M., OB BLK, AND		
(Unit P)	660'FS	L & 66	O'FEL		5 11 H 13 6 1		SURVEY OR AREA	L
		<u> </u>						7-S, R-29-Е
. PERMIT NO.				Show whether DF.	RT, GR, etc.)	12. 00	UNTY OR PARISE	18. STATE
			3	580'GR		Edo	ly	NM
		Check A	Appropriate Box 7	o Indicate Na	ature of Notice, Report,	or Other De	ata	
	NOT		ENTION TO:	1		BREQUENT REP		
TEST WATE	BBUT-OFF		PULL OR ALTER CAS		WATER SHUT-OFF			
FRACTURE T			MULTIPLE COMPLETI		FRACTURE TREATMENT	.	ALTERING C	
SHOOT OR A			ABANDON®		SHOOTING OR ACIDIZING	a	ABANDONME	
REPAIR WEL	.L		CHANGE PLANS					
					(Other)			
(Other) DESCRIBE PRO proposed nent to thi -21-85:	MIRU W scrape	SU. Pu r, WIH	lled rods and to 2975'. Ck	pump. In 'd TD w/ w	(NoTE: Report r Completion or Re details, and give pertinent ons and measured and true of stalled BOP. Pul vireline - 3210'.	dates, including vertical depths .led tbg. POH	port and Log for g estimated dat for all marker Picked up	rm.) te of starting any and sones perti-
(Other) DESCRIBE PRO proposed nent to thi 8-21-85:	MIRU W scrape PU 7" Set RB Pressu and te rate o	SU. Pu r, WIH RBP and P @ 29 red up sting T f 1 ¹ 2 B	lled rods and to 2975'. Ck d pkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus	(NoTE: Report r Completion or Re details, and give pertinent stalled BOP. Pul vireline - 3210'. Cested tbg to 5000 and on top of plu woved pkr up hole, in 7" casing @ 30' w/pkr set @ 32' f	completion Ber dates, including vertical depths POH psi above g and tes setting from sur	port and Log for g estimated dat for all marker ve slips w sted - ok. at differ cface. Es	rm.) e of starting any s and sones perti- o 7" csg while GIH. cent depths stablished
(Other) DESCRIBE PRO proposed nent to thi 3-21-85: 3-22-85:	MIRU W scrape PU 7" Set RB Pressu and te rate o up aro	SU. Pu r, WIH RBP and P @ 29 red up sting T f 1 ¹ 2 B	lled rods and to 2975'. Ck d pkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus	(NoTE: Report r Completion or Re details, and give pertinent ustalled BOP. Pul direline - 3210'. ested tbg to 5000 and on top of plu woved pkr up hole, in 7" casing @ 30'	completion Ber dates, including vertical depths POH psi above g and tes setting from sur	port and Log for g estimated dat for all marker ve slips w sted - ok. at differ cface. Es	rm.) e of starting any s and sones perti- o 7" csg while GIH. cent depths stablished
(Other) DESCRIBE PRO proposed nent to thi 3-21-85: 3-22-85: 3-22-85: 3-23 thru	MIRU W scrape PU 7" Set RB Pressu and te rate o up aro	SU. Pu r, WIH RBP and P @ 29 red up sting E 1 ¹ 2 B und ou	lled rods and to 2975'. Ck pkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow tside of 8-5/	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus 8" surface	(NoTE: Report r Completion or Re details, and give pertinent isstalled BOP. Pul vireline - 3210'. Sested tbg to 5000 and on top of plu noved pkr up hole, in 7" casing @ 30' w/pkr set @ 32' f casing. POH.	Led tbg. POH psi above g and tes from surfa	port and Log for g estimated dat for all marker ve slips w sted - ok. at differ cface. Es ace. Flui	rm.) e of starting any s and sones perti- o 7" csg while GIH. cent depths stablished d coming
(Other) DESCRIBE PRO proposed nent to thi 3-21-85: 3-22-85: 3-22-85: 3-22-85:	MIRU W scrape PU 7" Set RB Pressu and te rate o up aro Dug ou receiv	SU. Pu: r, WIH RBP and P @ 29 red up sting f 1 ¹ 2 B und ou t aroun	lled rods and to 2975'. Ck d pkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow tside of 8-5/ nd 8-5/8" cas v from around	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus 8" surface ing 3' bel bradenhea	(NoTE: Report r Completion or Re details, and give pertinent isstalled BOP. Pul direline - 3210'. Sested tbg to 5000 and on top of plu noved pkr up hole, in 7" casing @ 30' w/pkr set @ 32' f casing. POH. ow bradenhead. P d. Removed 8-5/8	completion Ber dates, including vertical depths POH psi above g and tes setting from surfa 'umped dow '' x 7'' br	port and Log for g estimated dat for all marker ve slips w sted - ok. at differ cface. Es ace. Flui m Z" casi cadenhead,	rm.) e of starting any s and sones perti- o 7" csg while GIH. cent depths stablished d coming
(Other) DESCRIBE PRO proposed nent to thi 3-21-85: 3-22-85: 3-22-85: 3-23 thru 3-27-85:	MIRU W scrape PU 7" Set RB Pressu and te rate o up arou Dug ou receive repair Instal	SU. Pu r, WIH RBP and P @ 29 red up sting f l ¹ 2 B und ou t aroun ed flow ed flow	Lled rods and to 2975'. Ck d pkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow tside of 8-5/ md 8-5/8" cas v from around /8" casing. v 8-5/8' x 7"	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus 8" surface ing 3' bel bradenhea Crew off 4 bradenhea	(NoTE: Report r Completion or Re details, and give pertinent isstalled BOP. Pul vireline - 3210'. Sested tbg to 5000 and on top of plu toved pkr up hole, in 7" casing @ 30' w/pkr set @ 32' f casing. POH. ow bradenhead. P d. Removed 8-5/8 8 hrs. SI 24 hrs d. Replaced 20#	completion Ber dates, including vertical depths POH psi above g and tes setting from surfa 'umped dow '' x 7'' br waiting c casing ni	port and Log for g estimated dat for all marker ve slips w sted - ok. at differ cface. Es ace. Flui m Z" casi cadenhead, on bradenh	rm.) e of starting any s and sones perti- o 7" csg while GIH. cent depths stablished d coming ing, head.
(Other) PESCRIBE PRO proposed nent to thi 3-21-85: 3-22-85: 3-23 thru 3-27-85: 3-28-85:	MIRU W scrape PU 7" Set RB Pressu and te rate o up aro Dug ou receiv repair Instal 7" wel	SU. Pul r, WIH RBP and P @ 29 red up sting f 1 ¹ 2 B und ou t aroun ed flow ed 8-5 Led new	Lled rods and to 2975'. Ck pkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow tside of 8-5/ nd 8-5/8" cas v from around /8" casing. v 8-5/8' x 7" Pressure te	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus 8" surface ing 3' bel bradenhea Crew off 4 bradenhea sted 7" ca	(NoTE: Report r Completion or Re details, and give pertinent isstalled BOP. Pul direline - 3210'. ested tbg to 5000 and on top of plu noved pkr up hole, in 7" casing @ 30' w/pkr set @ 32' f casing. POH. ow bradenhead. P d. Removed 8-5/8 8 hrs. SI 24 hrs d. Replaced 20# sing to 500#, ok.	completion Ber dates, including vertical depths POH psi above g and tes setting from surfa cumped dow " x 7" br waiting c casing ni	port and Log for g estimated dat for all marker Picked up te slips w sted - ok. at differ cface. Es ace. Flui on Z" casi cadenhead, on bradenh pple and	rm.) e of starting any and somes perti- o 7" csg while GIH. cent depths stablished d coming ing, head. installed
(Other) pescripe prod proved nent to thi 3-21-85: 3-22-85: 3-23 thru 3-27-85: 3-28-85:	MIRU W scrape PU 7" Set RB Pressu and te rate o up aro Dug ou receiv repair Instal 7" wel Instal	SU. Pul r, WIH RBP and P @ 29 red up sting f 1 ¹ ₂ Bi und ou t aroun ed flow ed 8-5 Led new Led new	Lled rods and to 2975'. Ck d pkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow tside of 8-5/ md 8-5/8" cas v from around /8" casing. v 8-5/8' x 7" Pressure te P. Pucked up	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus 8" surface ing 3' bel bradenhea Crew off 4 bradenhea sted 7" ca retrievin	(NoTE: Report r Completion or Re details, and give pertinent isstalled BOP. Pul direline - 3210'. Sested tbg to 5000 and on top of plu noved pkr up hole, in 7" casing @ 30' w/pkr set @ 32' f casing. POH. ow bradenhead. P d. Removed 8-5/8 8 hrs. SI 24 hrs d. Replaced 20# sing to 500#, ok. g tool, WIH and r	completion Ber dates, including vertical depths POH psi above g and tes setting from surfa cumped dow " x 7" br waiting c casing ni etrieved	port and Log for g estimated dat for all marker Picked up ye slips w sted - ok. at differ cface. Es ace. Flui on Z'' casi cadenhead, on bradenh pple and RBP, POH.	rm.) e of starting any s and sones perti- o 7" csg while GIH. cent depths stablished d coming .ng, head. installed
(Other) DESCRIBE PRO proposed nent to thi 3-21-85: 3-22-85: 3-23 thru 3-27-85: 3-28-85:	MIRU W scrape PU 7" Set RB Pressu and te rate o up aro Dug ou receiv repair Instal 7" wel Instal Ran mu	SU. Pul r, WIH RBP and P @ 29 red up sting f 1 ¹ ₂ Bi und ou t aroun ed flow ed 8-5 Led new lhead. Led BOI 1 ancho	lled rods and to 2975'. Ck pkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow tside of 8-5/ nd 8-5/8" cas from around /8" casing. v 8-5/8' x 7" Pressure te Pressure te Pressure te Pressure te Pressure te	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus 8" surface ing 3' bel bradenhea Crew off 4 bradenhea sted 7" ca retrievin g nipple o	(NoTE: Report r Completion or Re details, and give pertinent issand measured and true of stalled BOP. Pul direline - 3210'. Sested tbg to 5000 and on top of plu noved pkr up hole, in 7" casing @ 30' w/pkr set @ 32' f casing. POH. ow bradenhead. P d. Removed 8-5/8 8 hrs. SI 24 hrs d. Replaced 20# sing to 500#, ok. g tool, WIH and r n 2-3/8" producti	completion Ber dates, including vertical depths POH psi above g and tes setting from surfa cumped dow " x 7" br waiting co casing ni etrieved on tbg, S	port and Log for g estimated dat for all marker Picked up ye slips w sted - ok. at differ cface. Es ace. Flui adenhead, on bradenh cpple and RBP, POH. SN @ 3153'	rm.) e of starting any s and sones perti- o 7" csg while GIH. cent depths stablished d coming .ng, head. installed
(Other) DESCRIBE PRO proposed nent to thi 3-21-85: 3-22-85: 3-23 thru 3-27-85: 3-28-85:	MIRU W scrape PU 7" Set RB Pressu and te rate o up aro Dug ou receiv repair Instal 7" wel Instal Ran mu	SU. Pul r, WIH RBP and P @ 29 red up sting f 1 ¹ 2 Bi und ou t aroun ed flow ed 8-5 Led new Lhead. Led BOD d ancho 1 BOP a	lled rods and to 2975'. Ck pkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow tside of 8-5/ nd 8-5/8" cas from around /8" casing. v 8-5/8' x 7" Pressure te Pressure te Pressure te Pressure te Pressure te	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus 8" surface ing 3' bel bradenhea Crew off 4 bradenhea sted 7" ca retrievin g nipple o	(NoTE: Report r Completion or Re details, and give pertinent isstalled BOP. Pul direline - 3210'. Sested tbg to 5000 and on top of plu noved pkr up hole, in 7" casing @ 30' w/pkr set @ 32' f casing. POH. ow bradenhead. P d. Removed 8-5/8 8 hrs. SI 24 hrs d. Replaced 20# sing to 500#, ok. g tool, WIH and r	completion Ber dates, including vertical depths POH psi above g and tes setting from surfa cumped dow " x 7" br waiting co casing ni etrieved on tbg, S	port and Log for g estimated dat for all marker Picked up ye slips w sted - ok. at differ cface. Es ace. Flui adenhead, on bradenh cpple and RBP, POH. SN @ 3153'	rm.) e of starting any s and sones perti- o 7" csg while GIH. cent depths stablished d coming .ng, head. installed
(Other) PESCRIBE PRO proved nent to thi 3-21-85: 3-22-85: 3-22-85: 3-23 thru 3-27-85: 3-28-85:	MIRU W scrape PU 7" Set RB Pressu and te rate o up arou Dug ou receive repair Instal 7" wel Instal Ran mud Removed	SU. Pul r, WIH RBP and P @ 29 red up sting E 1 ¹ ₂ B und ou t aroun ed flow ed 8-5 Led new Lhead. Led BOD ancho i BOP a	lled rods and to 2975'. Ck lpkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow tside of 8-5/ md 8-5/8" cas v from around /8" casing. v 8-5/8' x 7" Pressure te P. Pucked up or and seatin and installed	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus 8" surface ing 3' bel bradenhea Crew off 4 bradenhea sted 7" ca retrievin g nipple o	(NoTE: Report r Completion or Re details, and give pertinent issand measured and true of stalled BOP. Pul direline - 3210'. Sested tbg to 5000 and on top of plu noved pkr up hole, in 7" casing @ 30' w/pkr set @ 32' f casing. POH. ow bradenhead. P d. Removed 8-5/8 8 hrs. SI 24 hrs d. Replaced 20# sing to 500#, ok. g tool, WIH and r n 2-3/8" producti	completion Ber dates, including vertical depths POH psi above g and tes setting from surfa cumped dow " x 7" br waiting co casing ni etrieved on tbg, S	port and Log for g estimated dat for all marker Picked up ye slips w sted - ok. at differ cface. Es ace. Flui adenhead, on bradenh cpple and RBP, POH. SN @ 3153'	rm.) e of starting any s and sones perti- o 7" csg while GIH. cent depths stablished d coming .ng, head. installed
(Other) DESCRIBE PRO proposed nent to thi 3-21-85: 3-22-85: 3-23 thru 3-27-85: 3-28-85: 3-29-85:	MIRU W scrape PU 7" Set RB Pressu and te rate o up aro Dug ou receiv repair Instal 7" wel Instal Ran muc Removed RD WSU	SU. Pul r, WIH RBP and P @ 29 red up sting f 1 ¹ ₂ Bi und ou t aroun ed flow ed 8-5 Led new Led new Led BOI d ancho d BOP a	lled rods and to 2975'. Ck l pkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow tside of 8-5/ nd 8-5/8" cas v from around (8" casing. v 8-5/8' x 7" Pressure te P. Pucked up or and seatin and installed	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus 8" surface ing 3' bel bradenhea Crew off 4 bradenhea sted 7" ca retrievin g nipple o	(NoTE: Report r Completion or Re details, and give pertinent issand measured and true of stalled BOP. Pul direline - 3210'. Sested tbg to 5000 and on top of plu noved pkr up hole, in 7" casing @ 30' w/pkr set @ 32' f casing. POH. ow bradenhead. P d. Removed 8-5/8 8 hrs. SI 24 hrs d. Replaced 20# sing to 500#, ok. g tool, WIH and r n 2-3/8" producti	completion Ber dates, including vertical depths POH psi above g and tes setting from surfa cumped dow " x 7" br waiting co casing ni etrieved on tbg, S	port and Log for g estimated dat for all marker Picked up ye slips w sted - ok. at differ cface. Es ace. Flui adenhead, on bradenh cpple and RBP, POH. SN @ 3153'	rm.) e of starting any s and sones perti- o 7" csg while GIH. cent depths stablished d coming .ng, head. installed
(Other) pescripe prod proved ment to thi 3-21-85: 3-22-85: 3-23 thru 3-27-85: 3-28-85: 3-28-85: 3-29-85:	MIRU W scrape PU 7" Set RB Pressu and te rate o up aro Dug ou receiv repair Instal 7" wel Instal Ran muc Removed RD WSU	SU. Pul r, WIH RBP and P @ 29 red up sting f 1 ¹ ₂ Bi und ou t aroun ed flow ed 8-5 Led new Led new Led BOI d ancho d BOP a	lled rods and to 2975'. Ck lpkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow tside of 8-5/ md 8-5/8" cas v from around /8" casing. v 8-5/8' x 7" Pressure te P. Pucked up or and seatin and installed	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus 8" surface ing 3' bel bradenhea Crew off 4 bradenhea sted 7" ca retrievin g nipple o wellhead.	(NoTE: Report r Completion or Re details, and give pertinent installed BOP. Pul direline - 3210'. Sested tbg to 5000 and on top of plu hoved pkr up hole, in 7" casing @ 30' w/pkr set @ 32' f casing. POH. ow bradenhead. P d. Removed 8-5/8 8 hrs. SI 24 hrs d. Replaced 20# sing to 500#, ok. g tool, WIH and r n 2-3/8" producti Ran 1-1/2" z 2"	<pre>completion Bey dates, including vertical depths .led tbg. POH 0 psi abov g and tes setting from surfa 'umped dow '' x 7'' br waiting c casing ni etrieved on tbg, S z 12' T.</pre>	port and Log for g estimated dat for all marker Picked up ye slips w sted - ok. at differ cface. Es ace. Flui ace. Flui adenhead, on bradenh pple and RBP, POH. SN @ 3153' B. pump.	rm.) e of starting any s and sones perti- o 7" csg while GIH. cent depths stablished d coming ing, head. installed
(Other) DESCRIBE PRO proposed nent to thi 8-21-85: 8-22-85: 8-23 thru 8-27-85: 8-28-85: 8-28-85: 8-29-85:	MIRU W scrape PU 7" Set RB Pressu and te rate o up aro Dug ou receiv repair Instal 7" wel Instal Ran muc Removed RD WSU	SU. Pul SU. Pul r, WIH RBP and P @ 29 red up sting f 1 ¹ / ₂ Bi and out t around t ar	lled rods and to 2975'. Ck pkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow tside of 8-5/ nd 8-5/8" cas v from around /8" casing. v 8-5/8' x 7" Pressure te P. Pucked up or and seatin and installed	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus 8" surface ing 3' bel bradenhea Crew off 4 bradenhea sted 7" ca retrievin g nipple o wellhead.	(NoTE: Report r Completion or Re details, and give pertinent issand measured and true of stalled BOP. Pul direline - 3210'. Sested tbg to 5000 and on top of plu noved pkr up hole, in 7" casing @ 30' w/pkr set @ 32' f casing. POH. ow bradenhead. P d. Removed 8-5/8 8 hrs. SI 24 hrs d. Replaced 20# sing to 500#, ok. g tool, WIH and r n 2-3/8" producti	<pre>completion Bey dates, including vertical depths .led tbg. POH 0 psi abov g and tes setting from surfa 'umped dow '' x 7'' br waiting c casing ni etrieved on tbg, S z 12' T.</pre>	port and Log for g estimated dat for all marker Picked up ye slips w sted - ok. at differ cface. Es ace. Flui ace. Flui adenhead, on bradenh pple and RBP, POH. SN @ 3153' B. pump.	rm.) e of starting any s and sones perti- o 7" csg while GIH. cent depths stablished d coming .ng, head. installed
(Other) DESCRIBE PRO proposed nent to thi 8-21-85: 8-22-85: 8-23 thru 8-23 thru 8-27-85: 8-28-85: 8-29-85: 1 hereby cere SIGNED	MIRU W scrape PU 7" Set RB Pressu and te rate o up aro Dug ou receive repair Instal 7" wel Instal Ran muc Remove RD WSU Job com	SU. Pul SU. Pul r, WIH RBP and P @ 29 red up sting E 1 ¹ ₂ Bi and out t around t aro	lled rods and to 2975'. Ck d pkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow tside of 8-5/ md 8-5/8" cas v from around /8" casing. v 8-5/8' x 7" Pressure te Pressure te Pressure te Pressure te Pressure te Pressure te Pressure te C. Pucked up or and seatin and installed	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus 8" surface ing 3' bel bradenhea Crew off 4 bradenhea sted 7" ca retrievin g nipple o wellhead.	(NoTE: Report r Completion or Re details, and give pertinent installed BOP. Pul direline - 3210'. Sested tbg to 5000 and on top of plu hoved pkr up hole, in 7" casing @ 30' w/pkr set @ 32' f casing. POH. ow bradenhead. P d. Removed 8-5/8 8 hrs. SI 24 hrs d. Replaced 20# sing to 500#, ok. g tool, WIH and r n 2-3/8" producti Ran 1-1/2" z 2"	<pre>completion Bey dates, including vertical depths .led tbg. POH 0 psi abov g and tes setting from surfa 'umped dow '' x 7'' br waiting c casing ni etrieved on tbg, S z 12' T.</pre>	port and Log for g estimated dat for all marker Picked up ye slips w sted - ok. at differ cface. Es ace. Flui ace. Flui adenhead, on bradenh pple and RBP, POH. SN @ 3153' B. pump.	rm.) e of starting any s and sones perti- o 7" csg while GIH. cent depths stablished d coming ing, head. installed
(Other) pescalae prod proved nent to thi 8-21-85: 8-22-85: 8-22-85: 8-23 thru 8-27-85: 8-28-85: 8-29-85: 1 hereby cert	MIRU W scrape PU 7" Set RB Pressu and te rate o up aro Dug ou receiv repair Instal 7" wel Instal Ran muc RD WSU Job cor	SU. Pul r, WIH RBP and P @ 29 red up sting f 1 ¹ ₂ Bi und ou t around ed flow ed 8-5 led new lhead. led BOD ancho i BOP a plete. Fregoing	lled rods and to 2975'. Ck d pkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow tside of 8-5/ nd 8-5/8" cas v from around /8" casing. v 8-5/8' x 7" Pressure te Pressure te Pucked up or and seatin and installed	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus 8" surface ing 3' bel bradenhea Crew off 4 bradenhea sted 7" ca retrievin g nipple o wellhead.	(NoTE: Report r Completion or Re details, and give pertinent installed BOP. Pul direline - 3210'. Sested tbg to 5000 and on top of plu hoved pkr up hole, in 7" casing @ 30' w/pkr set @ 32' f casing. POH. ow bradenhead. P d. Removed 8-5/8 8 hrs. SI 24 hrs d. Replaced 20# sing to 500#, ok. g tool, WIH and r n 2-3/8" producti Ran 1-1/2" z 2"	<pre>completion Bey dates, including vertical depths .led tbg. POH 0 psi abov g and tes setting from surfa 'umped dow '' x 7'' br waiting c casing ni etrieved on tbg, S z 12' T.</pre>	port and Log for g estimated dat for all marker Picked up ye slips w sted - ok. at differ cface. Es ace. Flui ace. Flui adenhead, on bradenh pple and RBP, POH. SN @ 3153' B. pump.	rm.) e of starting any s and sones perti- o 7" csg while GIH. cent depths stablished d coming ing, head. installed
(Other) DESCRIBE PRO proposed nent to thi 3-21-85: 3-22-85: 3-23 thru 3-23 thru 3-27-85: 3-28-85: 3-29-85: 1 bereby cert SIGNED (This space 1 APPROVED	MIRU W scrape PU 7" Set RB Pressu and te rate o up aro Dug ou receive repair Instal 7" wel Instal Ran muc RD WSU Job cor	SU. Pul r, WIH RBP and P @ 29 red up sting f 1 ¹ ₂ Bi und out t around ed flow ed 8-5 Led new Lhead. Led BOD 1 ancho 1 BOP a plete. Fregoing FTED F	lled rods and to 2975'. Ck d pkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow tside of 8-5/ md 8-5/8" cas v from around /8" casing. v 8-5/8' x 7" Pressure te Pressure te Pressure te Pressure te Pressure te Pressure te Pressure te C. Pucked up or and seatin and installed	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus 8" surface ing 3' bel bradenhea Crew off 4 bradenhea sted 7" ca retrievin g nipple o wellhead.	(NoTE: Report r Completion or Re details, and give pertinent installed BOP. Pul direline - 3210'. Sested tbg to 5000 and on top of plu hoved pkr up hole, in 7" casing @ 30' w/pkr set @ 32' f casing. POH. ow bradenhead. P d. Removed 8-5/8 8 hrs. SI 24 hrs d. Replaced 20# sing to 500#, ok. g tool, WIH and r n 2-3/8" producti Ran 1-1/2" z 2"	<pre>completion Bey dates, including vertical depths POH psi abov g and tes setting from surfa umped dow " x 7" br waiting c casing ni etrieved on tbg, S z 12' T. ialist p.</pre>	port and Log for g estimated dat for all marker Picked up ye slips w sted - ok. at differ cface. Es ace. Flui ace. Flui adenhead, on bradenh pple and RBP, POH. SN @ 3153' B. pump.	rm.) e of starting any s and sones perti- o 7" csg while GIH. cent depths stablished d coming ing, head. installed
(Other) DESCRIBE PRO proposed in nent to thi 3-21-85: 3-22-85: 3-22-85: 3-23 thru 3-27-85: 3-28-85: 3-29-85: 1 bereby cert SIGNED (This space 1	MIRU W scrape PU 7" Set RB Pressu and te rate o up aro Dug ou receive repair Instal 7" wel Instal Ran muc RD WSU Job cor	SU. Pul r, WIH RBP and P @ 29 red up sting f 1 ¹ ₂ Bi und out t around ed flow ed 8-5 Led new Lhead. Led BOD 1 ancho 1 BOP a plete. Fregoing FTED F	lled rods and to 2975'. Ck d pkr on 2-3/ 75'. Spotted on annulus, 7" casing. F PM @ 300# dow tside of 8-5/ nd 8-5/8" cas v from around /8" casing. v 8-5/8' x 7" Pressure te Pressure te Pucked up or and seatin and installed	pump. In 'd TD w/ w 8" tbg. T 2 sx of s leaking, m ound hole n annulus 8" surface ing 3' bel bradenhea Crew off 4 bradenhea sted 7" ca retrievin g nipple o wellhead.	(NoTE: Report r Completion or Re details, and give pertinent installed BOP. Pul direline - 3210'. Sested tbg to 5000 and on top of plu hoved pkr up hole, in 7" casing @ 30' w/pkr set @ 32' f casing. POH. ow bradenhead. P d. Removed 8-5/8 8 hrs. SI 24 hrs d. Replaced 20# sing to 500#, ok. g tool, WIH and r n 2-3/8" producti Ran 1-1/2" z 2"	<pre>completion Bey dates, including vertical depths POH psi abov g and tes setting from surfa umped dow " x 7" br waiting c casing ni etrieved on tbg, S z 12' T. ialist p.</pre>	Picked up ve slips w sted - ok. at differ cface. Es ace. Flui m Z'' casi cadenhead, on bradenh pple and RBP, POH. SN @ 3153' B. pump. ATE	rm.) e of starting any s and sones perti- o 7" csg while GIH. cent depths stablished d coming ing, head. installed

CARLSBAD, NEV. MCMICO Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.