

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APR 21 1997

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

N.M. Oil Cons.
811 S. 1st Street

Division
LC-28784C

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Marbob Energy Corporation

3. Address and Telephone No.

P. O. Drawer 227, Artesia, NM 88210 (505) 748-3303

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

990' FNL & 330' FWL Sec.26 T-17-S R-29-E Unit D

7. If Unit or CA, Agreement Designation

Burch Keely Unit

8. Well Name and No.

Burch Keely Unit #125

9. API Well No.

30-015-013138

10. Field and Pool, or Exploratory Area

Grbg Jackson SR Q GRBG SA

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 1) Spot 165 sx cmt, plug @ 3225', W.O.C., Tag cmt top @ 2496'
- 2) Load hole W/mud
- 3) Perforate 7" csg @ 755' base of salt, sqz W/50 sx cmt, W.O.C., Tag cmt top @ 602'
- 4) Perforate 7" csg @ 390' base of 8-5/8 shoe, sqz W/50 sx cmt W.O.C. Tag cmt top @ 325' Cement top too low, spot 20 sx cmt @ 325' bring cmt up to 225'. plug covered top of salt
- 5) Perforate 7" csg 50' circulate cmt to surface, leaving 7" csg full, set PA marker
- 6) Job completed 4-9-97

Port FD-2
4-25-97
P4A

14. I hereby certify that the foregoing is true and correct

Signed Raymond Maldonado

Title Supervisor

Date 04/11/97

(This space for Federal or State office use)

Approved by Raymond Maldonado

Title PETROLEUM ENGINEER

Date 4/23/97

Conditions of approval, if any: