

NMOCC COPY

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions on  
reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 028775

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Robinson Jackson Unit

8. FARM OR LEASE NAME

Tract 2

9. WELL NO.

15

10. FIELD AND POOL, OR WILDCAT

Eddyburg Jackson

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 27 - T17S - R29E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1. OIL ☐ GAS ☐  
WELL WELL OTHER Water Injection

2. NAME OF OPERATOR

Shenandoah Oil Corporation ✓

3. ADDRESS OF OPERATOR

P. O. Box 4534 - Odessa, Texas - 79760

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

1980' FNL and 1980' FEL Section 27 - T17S - R29E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3448 Gr.

O. C. C.  
ARTESIA, OFFICE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

## SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐PULL OR ALTER CASING ☐WATER SHUT-OFF ☐REPAIRING WELL ☒FRACTURE TREAT ☐MULTIPLE COMPLETE ☐FRACTURE TREATMENT ☐ALTERING CASING ☐SHOOT OR ACIDIZE ☐ABANDON\* ☐SHOOTING OR ACIDIZING ☐ABANDONMENT\* ☐REPAIR WELL ☐CHANGE PLANS ☐(Other) ☐

(Other)

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

1. Pulled tubing and packers
2. Set drillable CIBP @ 2300'
3. Perforated for squeeze @ 1755' and 1260'
4. (a) Set cement retainer @ 1700', cemented w/200 sx Class "C"  
(b) Set cement retainer @ 1194', cemented w/200 sx Class "C"  
(c) Retainer leaked or had another hole above retainer @ 1194'  
(d) Set cement retainer @ 1132' - cemented w/50 sx
5. Drilled out retainers and cemented to CIBP - tested - found small leaks @ 1743' and 1755'. Squeezed w/150 sx of Class "C". Drilled out and tested. Drilled out CIBP and circulated clean to 2864'.
6. Ran packers and tubing and put back on injection.

18. I hereby certify that the foregoing is true and correct

SIGNED

C. W. Downey, Jr.

TITLE

Acting District Engineer

DATE

4-13-78

(This space for Federal or State office use)

APPROVED BY

J. S. Lara

TITLE

ACTING DISTRICT ENGINEER

DATE

APR 26 1978

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

APR 20 1978

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO