



AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Continental Oil Company **Box C C, Hobbs, New Mexico**
Company or Operator Address
State P-27 Well No. **1** in **NW/4** of Sec. **27** T. **17-S**
Lease
R. **23-2** N. M. P. M., **Grayburg-Jackson** Field, **Eddy** County.
Well is **1900** feet south of the North line and **4620** feet west of the East line of **Section 27.**
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Address
If Government land the permittee is Address
The Lessee is Address
Drilling commenced **8-5** - 19 **46** Drilling was completed **10-9** - 19 **46**
Name of drilling contractor **Kincaid & Todd Drilling Company** Address **Dallas, Texas**
Elevation above sea level at top of casing **3542** feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from **2640** to **2660** No. 4, from to
No. 2, from **2665** to **2685** No. 5, from to
No. 3, from **2730** to **2850** No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from **240** to **245** feet. **HFV at 265' - unable to bail.**
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
	8-5/8" OD	278'	75	Halliburton		
	7" OD	2717'	100	" "		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters — Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Acid	5000 gal.		2717-2850	
		"	2000 "		2640-2660	
		"	2000 "		2665-2685	
		Nitro	200 quarts.		2790-2850	

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from **0** feet to **2900** feet, and from feet to feet

PRODUCTION

Put to producing **October 16,** 19 **46** ***(6 hour test pumped 27 bbls. oil.)**
The production of the first 24 hours was **148*** barrels of fluid of which **100** % was oil; % emulsion; % water; and % sediment. Gravity, Be.
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

G. C. Thalmon Driller **O. T. Mays** Driller
G. C. Pratt Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this **7** day of **March**, 19 **50**
J. D. McComish Notary Public
My Commission expires **5-17-53**
Name **Hobbs, New Mexico** **3-7-50**
Position **District Superintendent**
Representing **Continental Oil Company** Company or Operator
Address **Box CC, Hobbs, New Mexico**

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	10	10	Red sand
10	45	35	Red sand and shale
45	80	35	Red rock
80	120	40	Red shale
120	155	35	Red rock
155	165	10	Anhydrite and shale
165	175	10	Anhydrite
175	240	65	Red rock
240	245	5	Watersand
245	255	10	Red rock
255	435	180	Salt
435	485	50	Salt, anhydrite
485	505	20	Anhydrite
505	635	130	Salt
635	685	50	Salt, Anhydrite
685	730	45	Anhydrite
730	760	30	Anhydrite, lime
760	1780	1020	Anhydrite
1780	1799	19	Red sand
1799	2075	276	Anhydrite
2075	2900	825	Same - Total depth.

Plugged back to 2050.