

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Las CrucesLease No. 628775 (b)Unit W. 1/4 Sec. 27, T. 17S, R. 21E, S. 1**RECEIVED**

OCT 20 1960

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Hobbs, New Mexico July 29, 1960Well No. 32 is located 1900 ft. from N line and 1850 ft. from E line of sec. 22 27S 27 (1/4 Sec. and Sec. No.) 17S (Twp.) 21E (Range) 1 (Meridian)11000 (Field) 300 (County or Subdivision) 11000 (Section Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

7/28/60

DST No. 1 - 6060 to 6110' - Recovered 2' Drilling Mud- No show oil-gas or water 25 lb. Press.

DST No. 2 - 6390 to 6390' - Recovered 4613' Black Sulphur Salt Water- No oil or gas-

Initial Flow Press. 3795- Final P. Press. 3195.

TO PLUG & ABANDON- Set Cement Plug from 6000' to 6390' - Keeping hole full heavy mud-

do 2600' to 3400' do

do 15 lbs. in bottom of 7 5/8" Casing

do 15 lbs. cement plug in bottom of collar top of 7 5/8" Casing.

with "Regulation Marker" extending 4' above surface level.

7/29/60-

Filled hole with heavy mud- Spotted 21 lbs. Cement from 6000' to 6390'- Checked Shutoff- OK.

do Spotted 165 lbs. " from 3600' to 3400'- Keeping hole full

Spotted 15 lbs. Cement Plug 1/ 958 to 1018' & 15 lb. Cement in bottom Collar top 7 5/8" Casing.

w/ Regulation Marker extending 4' above surface level. Slugging. Abandoning. Complete.

Company Sinclair Oil Gas CompanyAddress 320 S. Broadway, Hobbs, N.M.

By _____

Title Asst. Mgr.